# 4525-SS5A030GP <

## MEAS | MEAS MS4525

TE Internal #: 4525-SS5A030GP Analog Pressure Sensor Modules, Gauge, 2.068 bar [30 psi], 10 -90% Vdc, ±0.25% Span Pressure Accuracy, Supply Voltage Range 5 V, MEAS MS4525

### View on TE.com >



Sensors > Pressure Sensors > Board Mount Pressure Sensors > PCB MOUNTED ANALOG PRESSURE SENSOR



Pressure Sensor Type: Analog Pressure Sensor Modules

Pressure Type: Gauge

Proof Pressure Range: 300 psi

Pressure: 2.068 bar [ 30 psi ]

Output Signal Type: 10 - 90% Vdc

# Features

# **Product Type Features**

 Sensor Package
 8 pin DIL

 Leg Style
 Through Hole

Pressure Sensor Type	Analog Pressure Sensor Modules
Pressure Type	Gauge
Electrical Characteristics	
Supply Voltage Range	5 V
Dimensions	
Product Width	17.4 mm[.685 in]
Product Length	12.7 mm[.5 in]
Product Height	11.7 mm[.46 in]
Usage Conditions	
Pressure	2.068 bar[30 psi]
Operating Temperature Range	-25 – 105 °C[-13 – 221 °F]
Operation/Application	
Proof Pressure Range	300 psi
Output Signal Type	10 - 90% Vdc
Pressure Accuracy	±0.25% Span

## 4525-SS5A030GP

Analog Pressure Sensor Modules, Gauge, 2.068 bar [30 psi], 10 - 90% Vdc, ±0.25% Span Pressure Accuracy, Supply Voltage Range 5 V, MEAS MS4525



### Packaging Features

Sensor Port Configuration	Single Sideport
Other	
Sensor Options	No Option

# **Product Compliance**

#### For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**




Also in the Series MEAS MS4525

**C** For support call+1 800 522 6752

## 4525-SS5A030GP

Analog Pressure Sensor Modules, Gauge, 2.068 bar [30 psi], 10 - 90% Vdc, ±0.25% Span Pressure Accuracy, Supply Voltage Range 5 V, MEAS MS4525





# **Customers Also Bought**





03P UMNL PLUG HSG RED

AVP19M CONC. AIO RGB R 500MM /1X6

=TE

# Documents

**CAD** Files

# 3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_4525-SS5A030GP\_C.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_4525-SS5A030GP\_C.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_4525-SS5A030GP\_C.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the  $\ensuremath{\text{Terms}}$  and  $\ensuremath{\text{Conditions}}$  of use.

# Datasheets & Catalog Pages

Data sheet

English

**&** For support call+1 800 522 6752

# 4525-SS5A030GP

Analog Pressure Sensor Modules, Gauge, 2.068 bar [30 psi], 10 - 90% Vdc, ±0.25% Span Pressure Accuracy, Supply Voltage Range 5 V, MEAS MS4525

