


			1	
	Part Number:		DRAWN	1/20/2017
	TC10	2803-1	CJ	
	IEIU		CHECKED	1/20/2017
			P.D	
	Description:	anical Transducer	APPROVED	1/20/2017
	Electro-Mecha		1.5	


This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com

## Top View

## Side View

## **Bottom View**





Items	Specifications	Conditions						
Sound Pressure Level	93	dB (@ 10cm)						
Resonant Frequency	2,830	Hz		REVISION HISTO	Y			
Rated Voltage	3.6	V	REV	DESCRIPTION	DATE	APPROVED		
Voltage Range	3 ~ 4.5	V		Released from Engineering	8/27/2014	J.S.		
Coil Resistance	18±5	Ω	1	Updated to new template	1/20/2017	J.S.		
Max. Rated Current	100	mA	2	Corrected voltage range and weight	5/18/2017	C.E.		
Storage Temperature	-40 ~ +85	°C		NOTES				
Operating Temperature	-20 ~ +70	°C		1) All dimensions are in mm unless otherwise noted				
Connection Method	Surface Pads			2) All tolerances are ± 0.2 mm unless otherwise noted				
Mount Type	Surface Mount			3) All parts meet RoHS				
Housing Material	LCP			4) Subject to change or redrawn without notice				
Weight	0.8	g						

Downloaded from Arrow.com.