
W31-X2M1G-40 <

Potter & Brumfield | Potter & Brumfield W23-31

TE Internal #: 4-1393247-1 Thermal, Series Trip, Silver, Operating Voltage 240 VAC, Operating Voltage 50 VDC, 40A Current Rating, Potter & Brumfield W23-31, Circuit Breakers

View on TE.com >

Relays & Contactors > Circuit Breakers



Circuit Breaker Type: Thermal

Circuit Function: Series Trip

Illuminated: Without

Actuator Color: Silver

Operating Voltage: 240 VAC

Features

Product Type Features

Circuit Breaker Style	Toggle
Illumination Type	No Light
Actuator Type	Push-Pull, Toggle



Circuit Breaker Type	Thermal			
Illuminated	Without			
Configuration Features				
	.47 (Diameter) in			
Circuit Function	Series Trip			
Number of Poles	1			
Electrical Characteristics				
Operating Voltage	50 VDC			
Current Rating	40 A			
Interrupt Capacity	1000A @ 50VDC or 240VAC			
Body Features				
Actuator Color	Silver			
Contact Features				
Trip Time at 200%	6 – 22 seconds			
Termination Features				

W31-X2M1G-40

Thermal, Series Trip, Silver, Operating Voltage 240 VAC, Operating Voltage 50 VDC, 40A Current Rating, Potter & Brumfield W23-31, Circuit Breakers



Terminal Configuration	8-32 Screws 90° to Each Other	
Mechanical Attachment		
Mounting Hardware Packaging	Assembled to Bushing	
Mounting Bushing	15/32-32 Threaded Bushing .32" Long Double "D", Silver Color	
Mounting Options	Two Hex Nuts/Lockwasher	
dentification Marking		
Stamped Marking Type	Amo Rata Marking	
	Amp Rate Marking	
Product Compliance For compliance documentation, visit the product page on TE.com>		
Product Compliance	Compliant with Exemptions	
Product Compliance For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU		

Halogen Content

Solder Process Capability

Cadmium oxide (10% in Component Part)

Pb (3.7% in Component Part)

Article Safe Usage Statements:

SVHC > Threshold:

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Not Low Halogen - contains Br or Cl > 900 ppm.

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

& For support call+1 800 522 6752

W31-X2M1G-40

Thermal, Series Trip, Silver, Operating Voltage 240 VAC, Operating Voltage 50 VDC, 40A Current Rating, Potter & Brumfield W23-31, Circuit Breakers





Also in the Series | Potter & Brumfield W23-31



Customers Also Bought



= TE			
TE Part #EM7080-000	TE Part #3-1393247-3	TE Part #34484	TE Part #7-1393246-1
THA-PDKG-07	W31-X2M1G-15=W23/W31	TERMINAL,SOLIS R 14-12 10	W23-X1A1G-30=W23/W31
THE STREET			
TE Part #3-1393247-1	TE Part #3-1393247-2	TE Part #4-1393247-3	TE Part #4-1393247-2
W31-X2M1G-1=W23/W31	W31-X2M1G-10=W23/W31	W31-X2M1G-50=W23/W31	W31-X2M1G-5=W23/W31



W31-X2M1G-40

Thermal, Series Trip, Silver, Operating Voltage 240 VAC, Operating Voltage 50 VDC, 40A Current Rating, Potter & Brumfield W23-31, Circuit Breakers



Documents

CAD Files 3D PDF

3D

Customer View Model

ENG_CVM_CVM_4-1393247-1_C_c-4-1393247-1-c.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_4-1393247-1_C_c-4-1393247-1-c.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_4-1393247-1_C_c-4-1393247-1-c.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages W23/31 Toggle or Pusl/Pull Actuator Thermal Circuit Breaker

English

W23/W31 Series Datasheet

English

Agency Approvals

UL

English