



Identification	Part No.	Drawing	Dimensions in mm
<p>Fibre optic cable, double ended, single mode</p> <p>Length: a = 1 m</p> <p>a = 5 m</p> <p>a = 10 m</p> <p>a = 20 m</p> <p>a = 40 m</p> <p>a = 50 m</p> <p>a = 100 m</p>	<p>33 58 211 0010 002</p> <p>33 58 211 0050 002</p> <p>33 58 211 0100 002</p> <p>33 58 211 0200 002</p> <p>33 58 211 0400 002</p> <p>33 58 211 0500 002</p> <p>33 58 211 1000 002</p>	<p>double ended</p> <p>a = length</p>	
<p>Fibre optic cable, single ended, single mode</p> <p>Length: a = 1 m</p> <p>a = 5 m</p> <p>a = 10 m</p> <p>a = 20 m</p> <p>a = 40 m</p> <p>a = 50 m</p> <p>a = 100 m</p>	<p>33 58 111 0010 002</p> <p>33 58 111 0050 002</p> <p>33 58 111 0100 002</p> <p>33 58 111 0200 002</p> <p>33 58 111 0400 002</p> <p>33 58 111 0500 002</p> <p>33 58 111 1000 002</p>	<p>Protection level: IP 65 / IP 67</p> <p>single ended</p> <p>a = length</p>	
<p>Fibre optic breakout cable, single mode</p> <p>Length: 10 m</p> <p>Length: 20 m</p> <p>Length: 100 m</p>	<p>33 58 751 0100 002</p> <p>33 58 751 0200 002</p> <p>33 58 751 1000 002</p>	<p>PUR jacket</p> <p>2-fibre single mode</p> <p>Outer diameter: 6.5 mm</p> <p>Min. bending radius: 10.4 cm</p> <p>Installation: 10.4 cm</p> <p>Operating: 5.2 cm</p>	