


- SPECIFICATIONS**
- 1、Current Rating: 2A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperatuer Range: -25℃~ +85℃
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000mΩ Min
 - 6、Withstanding Voltang: 800V AC/minute
 - 7、Material: Wafer LCP UL94-V0(2)
PIN Brass Tin-plated
Solder tad phosphoric bronze Tin-plated

Circuit	Part NO.	Dimensions mm			
		A	B	C	D
2	HC-1.25-2PWT-X	1.25	7.55	4.40	/
3	HC-1.25-3PWT-X	2.50	8.80	4.35	/
4	HC-1.25-4PWT-X	3.75	10.05	5.60	2.50
5	HC-1.25-5PWT-X	5.00	11.30	6.85	3.75
6	HC-1.25-6PWT-X	6.25	12.55	8.10	5.00
7	HC-1.25-7PWT-X	7.50	13.80	9.35	6.25
8	HC-1.25-8PWT-X	8.75	15.05	10.60	7.50
9	HC-1.25-9PWT-X	10.00	16.30	11.85	8.75
10	HC-1.25-10PWT-X	11.25	17.55	13.10	10.00
11	HC-1.25-11PWT-X	12.50	18.80	14.35	11.25
12	HC-1.25-12PWT-X	13.75	20.05	15.60	12.50
13	HC-1.25-13PWT-X	15.00	21.30	16.85	13.75
14	HC-1.25-14PWT-X	16.25	22.55	18.10	15.00
15	HC-1.25-15PWT-X	17.50	23.80	19.35	16.25
16	HC-1.25-16PWT-X	18.75	25.05	20.60	17.50

Ordering Information

HC-1.25 - N*** - *

Pin: 1-16
Type: 1-16
Colour: 1-16



		GENERAL TOLERANCE	制图 DRAWING	深圳市华灿天禄电子有限公司 ShenzhenhuaciantianluELECTRONICS CO.,LTD			
		DIM TOL	审核 CHECK				
		X.X ±0.30	批准 APPROVAL	产品名称 TITLE	1.25-卧贴	版本 REV.	A
		X.XX ±0.20	比例 SCALE	产品料号 PART NO.	HC-1.25-NPWT-X	单位 UNITS	mm
		X.XXX ±0.10	投影 Projection	材料 MATERIAL		页次 SHEET	1/1
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle ±3.0°				