






ROHS compliant



REV.	ECN NO.	DRAWN	DATE

**NOTES:**

**1.Specification :**

- 1> Operation force: 500gf Max.
- 2> Operation Temperature: -30 °C to +85°C.
- 3> Storage Temperature: -40 °C to +85°C.
- 4> Mechanical Life: 3000 cycles operations.
- 5> Resistance to Soldering: 260 ±5°C for 3-5 Seconds.

**2.PLATING:**

- 1> GOLD Flash 1u" (min) SOLDERTAIL,
- 3u" GOLD PLATING ON THE CONTACT AREA.

**3.ELECTRICAL:**

- 1> Non-switch Rating: 100mA at 50V DC.
- 2> Switching Rating: 25mA at 24V DC.
- 3> Contact Resistance: Initial 50mΩ Max. Contact Resistance: After life 100mΩ Max.
- 4> Insulation Resistance: 1000MΩ Min at 50VDC.
- 5> Dielectric Strength: 500V AC for 60seconds.
- 6> Switch Capacitance: 5PF Max at 1MHZ.

**4.PART NUMBER DESCRIPTION:**

DSPV XX L H G E T

**5.PACKAGE:** 27pcs/Tube, 1080pcs/Box.

东莞市康深电子科技有限公司  
KongShen Electronics TechnologyCorp.

Drawing	dengkg	Date	2012.03.25	LINER		ANGLES		PRODUCT Family	DSPV Series Pitch 2.54mm
Check	zhong	Scale	4:1	>0±0.05	>0° ±0.5°	PRAT NO.	DSPV07LHGET		
Approved		Unit	MM	>1±0.10	>5° ±1.0°	FILE NO.	KE-DSPV-007-A		
Size	A4	Rev.	A	>10±0.30		PROJECTION			