Product data sheet
Characteristics

NSYDCD2412
Cable entry system type Multi-CS dimensions 112 x 36 mm and 12 openings

Green Premium™

Overview

Lead time	Usually Ships within 4 Weeks

Main

Range	PanelSeT
Product or Component Type	Cable entry
Accessory / separate part category	Cable management accessory
Application	Multi-purpose
Mounting location	Enclosure bottom
Cable entry	12 grommets 0.08…0.5 in (2…12 mm)
Quantity per Set	Set of 1
Material	polypropylene

Complementary

Height	5.8 in (148 mm)
Width	2.3 in (58 mm)
Depth	0.7 in (18 mm)
Net Weight	0.452 lb(US) (0.205 kg)
Cut-out dimensions	112 x 36 mm

Environment

Resistance to chemical agents	Good resistant to alcohols Good resistance to mineral oils and greases Good resistance to weak acids and bases Good resistance to fuels
Flame retardance	V0 conforming to UL 94
Ambient Air Temperature for Operation	-22…212 °F (-30…100 °C)
IP degree of protection	IP65 IEC 60529

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606489429027
Returnability	No
Country of origin	FR

Life Is On | Schneider Electric

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.4 in (6.0 cm)
Package 1 Width	4.7 in (12.0 cm)
Package 1 Length	8.07 in (20.5 cm)
Package 1 Weight	6.8 oz (192.0 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	7.9 in (20.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	4.912 lb(US) (2.228 kg)
Unit Type of Package 3	PAM
Number of Units in Package 3	300
Package 3 Height	33.5 in (85.0 cm)
Package 3 Width	39.4 in (100.0 cm)
Package 3 Length	47.2 in (120.0 cm)
Package 3 Weight	173.81 lb(US) (78.84 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Life Is On | Schneider Electric