



PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 300V AC, DC
- 3、Temperatuer Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material: Wafer Nylon6T, UL94V-0
PIN Brass Tin-plated
Solder tab Brass Tin-plated

Circuit	Part NO.	Dimensions mm	
		A	B
2	HC-PAE-2ALT	2.00	8.00
3	HC-PAE-3ALT	4.00	10.00
4	HC-PAE-4ALT	6.00	12.00
5	HC-PAE-5ALT	8.00	14.00
6	HC-PAE-6ALT	10.00	16.00
7	HC-PAE-7ALT	12.00	18.00
8	HC-PAE-8ALT	14.00	20.00
9	HC-PAE-9ALT	16.00	22.00
10	HC-PAE-10ALT	18.00	24.00
11	HC-PAE-11ALT	20.00	26.00
12	HC-PAE-12ALT	22.00	28.00

			GENERAL TOLERANCE	制图 DRAWING	深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD			
			DIM TOL	审核 CHECK	产品名称 TITLE	PAE 立贴	版本 REV.	A
			X.X ±0.30	批准 APPROVAL	产品料号 PART NO.	HC-PAE-NALT	单位 UNITS	mm
1	初版发行		X.XX ±0.20	比例 SCALE	材料 MATERIAL		页次 SHEET	1/1
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	X.XXX ±0.10	投影 Projection				
			Angle ±3.0°					