



- [Circuit Board Indicators](#)
- [Panel Mount Indicators](#)
- [Solid State Lighting](#)
- [Traffic Signals](#)
- [Vehicle Lighting](#)
- [Rail](#)
- [Obstruction Lighting](#)
- [Hazardous Area Lighting](#)
- [Heliport Lighting](#)

how to purchase

- [sales contacts](#)
- [stock check](#)

search

Product Line Search

Please select a Product Line to search.

Circuit Board Indicators

find

Part # / Text Search

Part No.:

Text Search:

search

quick links

Dialight Corporate Video


Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes
FAQs

[Dialight Ltd \(UK\)](#)
[Dialight Garufo](#)
[Dialight BLP](#)
[LumiDrives](#)

| Circuit Board Indicators - Through Hole Indicators | |
|--|------------------------------|
| P/N# 5600503F | Bi-Pin LED Lamp Single Color |
| Description | Bi Pin LED Lamp |
| Package Options | 25 Pieces Per Bag |
| Product Type | Through Hole Indicators |
| Sub Product Type | Discrete LED |
| Configuration | Bi-Pin LED Lamp |
| Lamp Type | Single Color |
| Viewing | Top View |
| Viewing Angle | 24 |

| Absolute Maximum Ratings (T _a = 25 °) | |
|--|----------------|
| Operating Temp | -20 to +100° C |
| Storage Temp | -55 to +100° C |



Operating Characteristics

| | |
|----------------------------|--------------|
| LED Position | |
| Color | Green |
| Lamp Type | Single Color |
| LED Type | Resistor |
| Intensity Min (mcd) | |
| Intensity Typ (mcd) | 70.0 |
| Intensity Max (mcd) | |
| Fwd Voltage Min | |
| Fwd Voltage Typ | |
| Fwd Voltage Max | |
| Dom Wavelength Min (nm) | |
| Dom Wavelength Typ (nm) | |
| Dom Wavelength Max (nm) | |
| Power Dissipation Max (mW) | |
| Backlighting | |
| Pitch Between Vertical | |
| Pitch Between Horizontal | |
| Lum Intensity Min | |
| Lum Intensity Typ | |
| Lum Intensity Max | |

Distributor Stock Check

Check stock with our distributors now.

5600503F

[check stock](#)