Mini PushPull ix Industrial®





Ma	arb	2	0

- Automation
- **Machinery & Robotics**
- Transportation
- Energy

- Small Drives
- **Vibratory Conveyors**
- **Control Terminals**
- Passenger Information & **Entertainment Systems**

Applications

- Wireless Access Points
- Connections Inside Cabinets

Description

HARTING is pleased to announce the new Mini PushPull ix Industrial®. The new Mini PushPull represents the waterproof and dustproof version of the ix Industrial® Gbit Ethernet Interface. With a 30 % shorter housing compared to the proven HARTING PushPull RJ45, users benefit from a miniaturized data interface for demanding applications.

Links to Other Materials

https://www.harting.com/US/en/ix-Industrial

Specs

- IP 65/67
- Suitable for 10 Gbit/s Ethernet / Cat 6A
- 360° shielding
- Cable diameter 4.5-7.5 mm

- - AWG 26-28 (10 poles) stranded
 - Optical indicators for mating orientation
 - Integrated "Security Clip" in yellow color avoids unwanted operation

Feature

Advantages & Benefits

Mini PushPull IP 65/67

- Provides a high reliable connection even under high shock and vibration conditions
- 30% shorter compared to the RJ45 PushPull variant
- Provides a compact and dense solution within environments where space constraint is a challenge
- Visual identification via yellow tab of mating orientation
- Provides time saving during installation and deployment on the field

People | Power | Partnership