

备注 NOTE:

1.材质 MATERIAL:


- 1.1胶芯 INSULATOR: LCP+30%G.F
- 1.2端子 CONTACT: C7025, T=0.20mm;
Half-gold-plated matte tin 30U"
- 1.3外壳 SHELL: STEEL, T=0.15mm;
Nickel plated on the surface
- 1.4卡钩 Hook: STEEL, T=0.40mm;
Nickel plated on the surface

2.电气特性 ELECTRICAL CHARACTERISTICS :

- 2.1额定电流: 0.5A
- 2.2接触阻抗 CONTACT RESISTANCE: 40mΩ MAX
- 2.3绝缘阻抗 Insulation resistance: 100MΩ MIN 250V DC
- 2.4耐压测试 DIELECTRIC WITHSTANDING VOLTAGE : 100V AC
- 2.5沾锡性: 温度245±5℃, 时间5±0.5s
- 2.6整体插入力 Overall insertion force: 2.0kgf MAX
耐久前整体拔出力 Overall pull-out force before durability :0.8kgf MIN
耐久后整体拔出力 Overall pull-out force after durability:0.6kgf MIN
- 2.7使用寿命 DURABILITY: 10000次
- 2.8工作温度 OPERATING TEMPERATURE : -25℃~+80℃

A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1		
A7	DN1		
A9	VBUS	B4	VBUS
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

U261-16XN-4BJ124



					DSND		DATE		SCALE: N/A	MODEL TYPE: 3.1 TYPE C			
					ΔX		DATE		VIEW:	PART NO.:			
					ΔX		DATE		UNIT: mm/in	DWG NO.:			
					ΔX		DATE		SIZE: A4	U261-16XN-4BJ124			
MARK					DESCRIPTION	DATE	REVISED	APPROVED		WEIGHT	SHEET	REVISION	
					REVISIONS	UNSPECIFIED TOLERANCES				XKB INDUSTRIAL PRECISION CO.,LIMITED	1.0g	1/1	A0
					www.xk-dg.cn www.helloxkb.com www.helloxkb.cn								