



Main

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	3L
Total number of 18 mm modules	57

Complementary

Number of ways	19 ways 3 L
Poles configuration for 1 way	1 x 3P
Connection pitch	18 mm
Connector type	Tooth
Distance between way	54 mm
Marking	L1 L2 L3
Insulation	Insulated
Device presentation	Cutttable
Provided equipment	End piece : set of 10
[Ie] rated operational current	100 A (40 °C)
System Voltage	415 V AC
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
Mounting location	Top or bottom on tunnel type terminals Top or bottom on double terminal
9 mm pitches	114
Width	39.37 in (1000 mm)
Colour	White (RAL 9003)
Range compatibility	Multi 9 C60 Acti 9 iK60 Acti 9 iC60 Acti 9 iID Acti 9 iID K Acti 9 iSW Acti 9 iSW-NA

Environment

standards	IEC 61439-2 IEC 60947-7-1
fire resistance	1760 °F (960 °C) (30 s) conforming to IEC 60695-2-1
pollution degree	3 conforming to IEC 60947-7-1
IP degree of protection	IP20 with end-pieces and tooth covers

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1336 - Schneider Electric declaration of conformity	Compliant - since 1336 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

Available

Available

Need no specific recycling operations

Need no specific recycling operations
