

SITOP BATTERY MODULE/24V/1.2AH



SITOP rechargeable battery module 24 V/1.2 Ah with maintenance free Sealed lead batteries for SITOP DC-USV Module 6 A

Charging current charging voltage	
end-of-charge voltage at DC	
<ul style="list-style-type: none"> at -10 °C recommended at 0 °C recommended at 10 °C recommended at 20 °C recommended at 30 °C recommended at 40 °C recommended at 50 °C recommended 	29 V 28.4 V 27.8 V 27.3 V 26.8 V 26.6 V 26.3 V
Output	
Permissible charging current, max.	0.3 A
Rated voltage Vout DC	24 V
Safety	
Short-circuit protection	Battery fuse 7.5 A/32 V (solid-state circuitry blade-type fuse + support)
design of the overload protection	Valve control
Safety	
Protection class	Class III
Degree of protection (EN 60529)	IP00
Approvals	
CE mark	Yes
UL/cUL (CSA) approval	cURus-Recognized (UL 1778, CSA C22.2 No. 107.1), File E219627
Marine approval	DNV GL, ABS
environmental conditions	
Operating data note	For storage, mounting and operation of lead-acid batteries, the relevant DIN/VDE regulations or country-specific regulations (e.g. VDE 0510 Part 2/EN 50272-2) must be observed. You must ensure that the battery site is sufficiently ventilated. Possible sources of ignition must be at least 50 cm away.
ambient temperature	
<ul style="list-style-type: none"> during operation during transport during storage 	-15 ... +50 °C -20 ... +50 °C -20 ... +50 °C
relative temporary capacity loss at 20 °C in a month typical	3 %

Service life	
service life of energy storage	capacity falls to 80 % of original capacity (according to EUROBAT)
<ul style="list-style-type: none"> • typical note • at 20 °C typical • at 30 °C typical • at 40 °C typical • at 50 °C typical 	4 y 2 y 1 y 0.5 y
ambient temperature during storage note	Along with the storage and operating temperature, other factors such as the duration of the storage period and the charge status during storage have a decisive influence on the possible useful life. Batteries should therefore be stored as briefly as possible, always fully charged, and within the temperature range 0 to +20 °C.
Mechanics	
Connection technology	spring-loaded terminals
Connection for power supply unit	1 screw terminal each for 0.08 ... 2.5 mm ² for + BAT and - BAT
product component included	Accessories pack with solid-state circuitry fuse 7.5 A
width of the enclosure	96 mm
height of the enclosure	106 mm
depth of the enclosure	108 mm
installation width	116 mm
Installation height	126 mm
Weight, approx.	1.8 kg
Installation	snaps onto DIN rail EN 60715 35x7.5/15 or keyhole mounting for hooking in to M4 screws
number of cells	12
Battery	1.2 A·h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

