

**Catalog No. 5357**

**Description: 2INCH INSUL 90 DEGREE LIQ TIGHT CON**

**UPC No 786210053578**

**Home > Cable Protection Systems > T&B Liquidtight Fittings > Liquid tight connectors**

2 Inch 90 Degree Malleable Iron Insulated Liquidtight Connector



**Descriptors**

Category	Liquid tight connectors
Type	Connectors-90 Degree
Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.

**Specifications**

Material	Malleable Iron
Finish	Electro Zinc Plated/Chromate Coating

**Classifications**

Brand Name	T&B Liquidtight Fittings
Standard	UL E23018, CSA

**Dimensions**

Size	2 Inch
------	--------

**Compliance and Certifications**

RoHS	RoHS3 Compliant
REACH SVHC	REACH 223 Compliant
TSCA	TSCA Section 6(h) Compliant

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	2 inch
Model	90°-elbow
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Thread
Thread type	NPT

ETIM	EC001180 Screw connection for protective metallic hose
Thread connection size	Other
One-piece	N
Material housing	Other
Approved in combination with protective conduit CSA	Y
Approved in combination with protective conduit UL	Y