

Part Number: 1200668897

Product Description: Micro-Change (M12) Double-Ended Cordset with Knurled Hexnut, 8 Poles, Male (Straight) to Female (Straight), 24 AWG, Black TPU WSOR Cable, 2.0m (6.56')

Length

Series Number: 120066

Product Category: Circular Industrial

Cordsets

Status: Active

Engineering Number: 888030B41M020

Documents & Resources

Drawings

Drawing 1200668897_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---|
| China RoHS | Not Relevant |
| EU ELV | Compliant with Exemption 3 per 2000/53/EC |
| Low-Halogen Status | Not Relevant |
| REACH SVHC | Contains Lead per D(2024)4144- DC (27 June 2024) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|---|
| Category | Circular Industrial Cordsets |
| Series | 120066 |
| Description | Micro-Change (M12) Double-Ended Cordset with Knurled Hexnut, 8 Poles, Male (Straight) to Female (Straight), 24 AWG, Black TPU WSOR Cable, 2.0m (6.56') Length |
| IP Rating | IP67 |
| Product Family | Brad M8 and M12 Cordsets with Knurled Hexnuts and WSOR Cable |
| Product Name | Micro-Change (M12) |
| Region | Europe |
| Туре | Double Ended |
| UPC | 889056027328 |

Agency

| UL | E152210 |
|----|---------|
| | |

Electrical

| Current - Maximum per Contact | 2.0A |
|-------------------------------|------|
| Voltage - Maximum | 30V |

Physical

| Cable Diameter | 6.40mm (.252") |
|-------------------------|--------------------------|
| Cable Length | 2.0m (6.56') |
| Color - Cable Jacket | Black |
| Connector End A | Micro-Change (M12) |
| Connector End B | Micro-Change (M12) |
| Coupling Style | Knurled Hexnut, Threaded |
| Gender | Female-Male |
| Keyway | Single |
| LED Indicator | No |
| Material - Cable Jacket | TPU |

| Material - Connector Body | TPU |
|-------------------------------|----------------------|
| Material - Contact | Brass |
| Material - Coupling Nut | Nickel-plated Brass |
| Material - O-Ring | Fluoro-elastomer |
| Material - Plating Mating | Gold |
| Net Weight | 144.300/g |
| Orientation | Straight to Straight |
| Poles | 8 |
| Temperature Range - Operating | -25° to +85°C |
| Wire/Cable Type | UL 21215 |
| Wire Size (AWG) | 24 |

This document was generated on Sep 16, 2024