




Specifications:

规格:

- Voltage rating: 100V AC/DC
- 额定电压: 100V AC/DC
- Current rating: 3A AC/DC
- 额定电流: 3A AC/DC
- Withstanding voltage: 1000V AC/minute
- 耐受电压: 1000V AC/分钟
- Temperature range: -25°C~+85°C
- 温度范围: -25°C~+85°C
- Insulation resistance: 1000MΩ min
- 绝缘电阻: 1000MΩ Min
- Contact resistance: 20mΩ Max
- 接触电阻: 20mΩ Max

K 205001 T M - P SN
 ① ② ③ ④ ⑤ ⑥

- 1.K-XKBTEK-Car Connector
- 2.XKB Series No
- 3.Category:T-Terminal
- 4.Category:M-Male Terminal
- 5.Material:P-Phosphor Bronze
- 6.Plating:SN-Plated Tin



K205001TM-PSN	Phosphor Bronze	AWG#22-26	K205001HF
PART NO	Material	Wire Range	Suitable XKB Housing

DSND	SCALE: N/A	MODEL TYPE: 2.0mm automotive connector
DWN	VIEW:	PART NO.: K205001TM-PSN
CHKD	UNIT: mm/in	DWG NO.: X-K205001TM-PSN
APPD	SIZE: A4	

					ANGULAR	±5°
ΔX					L ≤ 4	±0.2
ΔX					4 < L ≤ 16	±0.3
ΔX					16 < L ≤ 63	±0.4
MARK	DESCRIPTION	DATE	REVISED	APPROVED	L > 63	±0.5
REVISIONS					UNSPECIFIED TOLERANCES	
www.helloxkb.com www.helloxkb.cn www.xk-dg.cn						



XKB INDUSTRIAL PRECISION CO., LIMITED

WEIGHT	SHEET	REVISION
	1/1	A0