



**Part Number :** [532590929](#)  
**Product Description :** Mighty-SPOX Header, 3.50mm Pitch, Right-Angle, 9 Circuits, Brass (CuZn) Contact  
**Series Number :** 53259  
**Status :** Active  
**Product Category :** PCB Headers and Receptacles



## Documents & Resources

### Drawings

[Drawing 532590929\\_sd.pdf](#)

### 3D Models and Design Files

[3D Model 532590929\\_stp.zip](#)

### Specifications

[Packaging Specification SPK-53259-001-001.pdf](#)

[Product Specification PS-51067-019-001.pdf](#)

## Product Environment Compliance

### Compliance

|                    |   |
|--------------------|---|
| GADSL/IMDS         | Compliant with Exemption 44; 33                 |
| China RoHS         |   |
| EU ELV             | Not Relevant                                    |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21              |
| REACH SVHC         | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS            | Compliant per EU 2015/863                       |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

---

### Part Details

#### General

|                |   |
|----------------|---|
| Status         | Active  |
| Category       | PCB Headers and Receptacles   |
| Series         | 53259   |
| Description    | Mighty-SPOX Header, 3.50mm Pitch, Right-Angle, 9 Circuits, Brass (CuZn) Contact |
| Application    | Power, Wire-to-Board  |
| Component Type | PCB Header  |
| Product Family | Mighty-SPOX Connector System  |
| Product Name   | Mighty-SPOX   |
| UPC            | 822348135448  |

#### Agency

|     |         |
|-----|---------|
| CSA | LR19980 |
| UL  | E29179  |

#### Electrical

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 5.5A |
| Voltage - Maximum             | 250V |

#### Physical

|                                |       |
|--------------------------------|-------|
| Breakaway                      | No    |
| Circuits (Loaded)              | 9     |
| Circuits (maximum)             | 9     |
| Durability (mating cycles max) | 30    |
| First Mate / Last Break        | No    |
| Flammability                   | 94V-0 |
| Glow-Wire Capable              | No    |

|                                |                |
|--------------------------------|----------------|
| Guide to Mating Part           | Yes            |
| Keying to Mating Part          | Yes            |
| Lock to Mating Part            | Yes            |
| Material - Metal               | Brass          |
| Material - Plating Mating      | Tin            |
| Material - Plating Termination | Tin            |
| Net Weight                     | 2523.800/mg    |
| Number of Rows                 | 1              |
| Orientation                    | Right Angle    |
| Packaging Type                 | Tray           |
| PC Tail Length                 | 3.50mm         |
| PCB Locator                    | Yes            |
| PCB Retention                  | None           |
| PCB Thickness - Recommended    | 1.60mm         |
| Pitch - Mating Interface       | 3.50mm         |
| Polarized to PCB               | Yes            |
| Shrouded                       | Fully          |
| Stackable                      | No             |
| Temperature Range - Operating  | -40° to +105°C |
| Termination Interface Style    | Through Hole   |

---

## Mates With / Use With

### Mates with Part(s)

| Description                        | Part Number  |
|------------------------------------|--------------|
| Mighty-SPOX Female Crimp Terminals | <u>50217</u> |
| Mighty-SPOX Receptacle Housings    | <u>51067</u> |