



Product: <u>5202UE</u> ☑

Security & Sound, #16-4c, BC, CMR

Product Description

Security & Sound Cable, Riser-CMR, 4-16 AWG stranded bare copper conductors with polypropylene insulation, PVC jacket with ripcord

Technical Specifications

Product Overview

Suitable Appli	cations:	Securit	y System, In	tercom/PA, Audio/Sp			
Constructi	on Details						
Conductor							
Element	No. of Elements	Size	Stranding	Material			
Conductor(s)	4	16 AWG	19x29	BC - Bare Copper			

Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code		
Conductor(s)	PO - Polyolefin	0.008 in (0.20 mm)	0.073 in (1.9 mm)	Black, Red, White, Green		

Outer Jacket

	Material	Nom. Thickness	Nom. Diameter	Ripcord
1	PVC - Polyvinyl Chloride	0.017 in (0.43 mm)	0.210 in (5.33 mm)	Yes
(Overall Cable Diameter (Nominal): 0.210 in (5.33 mm)	

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current	
Conductor(s)	4.2 Ohm/1000ft	23 pF/ft (75 pF/m)	5.0 Amps per conductor @ 25°C	

Voltage

UL Voltage Rating 300 V (CMR)

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	-20°C to +75°C

Bend Radius

Stationary Min.	Installation Min.
1 in (E2 mm)	2.1 in (F2 mm)
2.1 in (53 mm)	2.1 in (53 mm)
Max. Pull Tension	on:
Bulk Cable Weig	ght:

Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Reaction to Fire:	UL 1666 Riser, FT4, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMR
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6202UE

History

Update and Revision:	Revision Number: 0.445 Revision Date: 03-04-2023	

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC/EAN	Footnote
5202UE 010500	Black			612825157960	С
5202UE 010U1000	Black			612825157953	
5202UE 0081000	Gray			612825157922	С
5202UE 008500	Gray			612825157939	
5202UE 008U1000	Gray			612825336587	
5202UE 008U500	Gray			612825157915	
5202UE.00152	Gray	Reel	152 m	8719605008107	
5202UE.00305	Gray	Reel	305 m	8719605008114	
5202UE.00U305	Gray	Reel	305 m	8719605008121	
5202UE 009U1000	White			612825157946	

© 2024 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.