

Datasheet

Item No. R2.067.0310.0

Timer relay NGZ310 10S AC/DC 24-240V 50-60HZ (A)

NGZ310, OFF-delay single-range timer relay with auxiliary supply, 1 change-over contact, 0,5s - 10s, AC/DC 24-240 V 50-60Hz



Item No.	R2.067.0310.0
EAN	4015573815315
order unit	1 Piece(s)

Approvals



Technical data

General

Connection type	Screw connection
Plug-in socket	No
Remote operation possible	No
Only for remote control	No
Function flashing, starting with pause, fixed time	No
Function flashing, starting with pulse, fixed time	No
Clock function, starting with pause, variable	No
Clock function, starting with pulse, variable	No
Number of relay outputs, undelayed, change-over contacts	0
Relay outputs, delayed/undelayed selectable	No
Number of relay outputs, undelayed, normally closed	0
Number of relay outputs, undelayed, normally open	0
Number of relay outputs, delayed, change-over contacts	1
Number of relay outputs, delayed, normally open	0
Semiconductor output	No
Function delay-on energization	No
Function floating contact on energization	No
Function star-delta	No
Function delay on de-energization	Yes

Function floating contact on de-energization	No
Function pulse shaping	No

Technical data

With auxiliary voltage	Yes
Min. rated AC voltage for controls, 50 Hz	24 V
Max. rated AC voltage for controls, 50 Hz	230 V
Min. rated AC voltage for controls, 60 Hz	24 V
Max. rated AC voltage for controls, 60 Hz	230 V
Min. rated DC voltage for controls	24 V
Max. rated DC voltage for controls	230 V
Nominal voltage AC 50 Hz	24 V
Nominal voltage AC 60 Hz	24 V
Min. nominal voltage DC	24 V
Min. rated frequency	60 Hz
Max. rated frequency	50 Hz
Min. adjustable time	0.5 sec
Max. adjustable time	10 sec

Dimensions

Depth	98 mm
Width	22.5 mm
Height	83 mm