



RECOMMENDED PCB LAYOUT
TOLERANCE:±0.05

表面处理
PLATED
料厚
THICKNESS
材料
MATERIAL

规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: Current Rating
1.0A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
50 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
300 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
100MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: Connector Mate and Umate Force
Mate force: 3.0kgf (MAX)
Umate force: 0.7kgf (MIN)
2. 端子保持力: Terminal Retention
0.5kgf (MIN)

原材料: Material:

1. 塑胶: Housing:
Hing Temperature Ternmaplastics,
UI 94V-0 LCP Black
 2. 端子: Contact: Copper Alloy H65-EH
 3. 外壳: Shell: H65-H
- 电镀: Finish:
1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
 2. 外壳: Shell:
Nickel Plating (能过炉自动上锡)

GENERAL TOLERANCES		III	II	I
CALLS		±0.03	±0.02	±0.01
X.XXX		±0.08	±0.06	±0.04
X.XX		±0.10	±0.08	±0.05
X.X		±0.12	±0.10	±0.07
X		±0.20	±0.16	±0.10
ANGLE		±1.0°	±1.0°	±2.0°
版次 REV.	A/0			
单位 UNIT	1:1			
比例 SCALE	1:1			

品名 TITLE	料号 P.C. NO.	图号 REV. NO.	图名 REV. NAME
MI1000 USB 08 B TYPE 0.45mm 脚长1.25mm 平口 长针	XXXXXXXXXX	USB-MIR-D-021	
德艺隆电子有限公司	绘图 DRAWN	审核 CHECKED	批准 APPROVED
页次 PAGE	1/1	路径 FILE NAME	