


NOTES: UNLESS OTHERWISE SPECIFIED


MATERIAL:
 HOUSING: THERMOPLASTIC; BLACK
 SEAL: SILICONE RUBBER


- 2. MODIFICATIONS: THREADED ADAPTER;
- 3. SPECIFICATIONS:
 - 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
 - 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
 - 3.4 MOISTURE RESISTANCE: IP67&IP69K (MATED CONDITION).
 - 3.5 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDP04-18-08S* (* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL	CURRENT
SIZE	O.D.	O.D.	WIRE RANGE	RATING
12	2.46 mm (.097 in)	4.01 mm (.158 in)	10-14 AWG	

	REVISIONS				
REV	ECO	DESCRIPTION	DATE	BY	APPR
A1		RELEASE NEW DRAWING	06JAN18	Jony	TOMMY





	AHDP06-1	8-08PR-WTA					
	PART N	NUMBER		DESCRIPTION			ITEM
QUANTITY		MA	TEF	RIAL	S LI	ST	
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC +0.30		SIGNATUR DRAWN: JONY	es da 06JA	_	Α	mphenol	
2 PL DEC ±0.15 3 PL DEC ±0.08 3) Note reference	CHECKED: 01:05 Angles ±1" CHECKED: 01:01 06JAN18 Sine Systems - www.amphenc detereference =		e Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MI 48036	_			
MATERIAL SPECIFICATIONS:		APPROVAL: Tommy CUSTOMER: THIS DRAWING IS SUPPI				IG,18-08 POS,PIN CONTACT CED DIA. SEAL, AHDP SERIES	
PROCESS SPECIFICATIONS:		INFORMATION ONLY, DE SPECIFICATIONS AND PI SHOWN HEREON ARE TH THE AMPHENOL CORPO OF REPRODUCTION ARE DIMENSIONS ARE SUBJE	ERFORMANCE HE PROPERTY RATION, NO RI IMPLIED, ALL	DATA SIZE OF GHTS B	C-	AHDP06-18-08PR-WTA	A1
NEXT ASSY:		MANUFACTURING VARIA	RIATIONS.		NONE	SHEET 1 OF	1

A Series™ - Contact Size 12 Options (Works with: AHD-6, ATP, ATHD, DuraMate and PanelMate Series)

Machined Contacts, Sockets & Pins					
Part Number	Description	Size	AWG	Туре	
*AT60-204-12141-10	Male Contact - Pin, Nickel-plated	12	10-12	Machined	
*AT62-203-12141-10	Female Contact - Socket, Nickel-plated	12	10-12	Machined	
AT60-220-1231	Male Contact - Pin, Gold-plated	12	12-14	Machined	
AT62-210-1231	Female Contact - Socket, Gold-plated	12	12-14	Machined	
AT60-204-12141	Male Contact - Pin, Nickel-plated	12	12-14	Machined	
AT62-203-12141	Female Contact - Socket, Nickel-plated	12	12-14	Machined	

^{*}Works with ATP Series only

	DiagnosticGrade™ Machined Contacts, Sockets & Pins • Smaller AWG for Diagnostic Applications • Gold-plated • Increased Mating Cycles • Cost-effective				
	Part Number Description		Size	AWG	Туре
Γ	65-54749	Male Contact - DiagnosticGrade™, Pin, Gold-plated	12	20	Machined
	AT62-210-1231-1820	Female Contact - DiagnosticGrade™, Socket, Gold-plated	12	20	Machined

	Tooling - Machined Contacts		
Part Number	Part Number Description		
AUTK-12	Hand Crimp Tool, Size 12		
AUTK-100 Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20			
CA-5D12 Universal Hand Crimp Tool, Size 12/16/20			
CA-5E12	Pneumatic Crimp Tool, Size 12/16/20		
M300-25A	Hand Crimp Tool used with Crimp Locator MFX-3966, Size 12, 10AWG		
MFX-3966	Contact Locator used with Hand Crimp Tool M300-25A, Size 12, 10AWG		

Con	Contact Removal Tools (For both Machined or Stamped & Formed Contacts)		
Part Number Description			
ATRT-100	Contact and Wedgelock Extraction Tool		
AT11-337-1205 Contact Removal Tool, Plastic, Size 12			

	Sealing Plugs (For both Machined or Stamped & Formed Contacts)		
Part Number	Part Number Description		
A114017	Sealing Plug, Size 12, White		

Stamped & Formed Contacts, Sockets & Pins						
Part Number	Description	Size	AWG	Туре		
AT60-12-0244	Male Contact - Pin, Gold-plated	12	10-12	Stamped & Formed		
AT62-12-0244	Female Contact - Socket, Gold-plated	12	10-12	Stamped & Formed		
AT60-12-0222	Male Contact - Pin, Nickel-plated	12	10-12	Stamped & Formed		
AT62-12-0222	Female Contact - Socket, Nickel-plated	12	10-12	Stamped & Formed		
AT60-12-0144	Male Contact - Pin, Gold-plated	12	12-14	Stamped & Formed		
AT62-12-0144	Female Contact - Socket, Gold-plated	12	12-14	Stamped & Formed		
AT60-12-0166	Male Contact - Pin, Nickel-plated	12	12-14	Stamped & Formed		
AT62-12-0166	Female Contact - Socket, Nickel-plated	12	12-14	Stamped & Formed		

	Tooling - Stamped & Formed Contacts			
Part Number	Part Number Description			
MFX-3973	Crimp Die - Size 12			
MFX-3985	Crimp Die - Svize 12, 10-12AWG -02XX Series			
ATT-12-00	Hand Crimp Tool - Size 12, 12AWG			
ATT-12-01	Hand Crimp Tool - Size 12, 10AWG			