

Cable tie - WT-HT HF 3,6X200 BK - 3240785

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)



Image shows WT-HT HF 4.8x200 BK version



Key Commercial Data

| Packing unit | 1 pc |
|--------------------------------------|----------|
| Minimum order quantity | 100 pc |
| Weight per Piece (excluding packing) | 0.8 g |
| Custom tariff number | 39269097 |
| Country of origin | Croatia |

Technical data

Dimensions

| Length (b) | 200 mm |
|----------------|------------|
| Width (a) | 3.6 mm |
| Cable diameter | 3 mm 50 mm |

Ambient conditions

| Ambient temperature (operation) | -40 °C 125 °C |
|---|--|
| Ambient temperature (assembly) | -10 °C 60 °C |
| Optimum ambient temperature (storage/transport) | 23 °C 50 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, avoid direct sunlight, avoid direct heat. |
| Short-term temperature | 145 °C |



Cable tie - WT-HT HF 3,6X200 BK - 3240785

Technical data

General

| Color | black |
|--|--------------------------------|
| Туре | Internal teeth |
| Components | free from silicone and halogen |
| Flammability rating according to UL 94 | V2 |
| Material | PA 6.6 |
| Standards and Regulations | |
| Flammability rating according to UL 94 | V2 |

Classifications

eCl@ss

| eCl@ss 4.0 | 27140702 |
|------------|----------|
| eCl@ss 4.1 | 27140702 |
| eCl@ss 5.0 | 27140702 |
| eCl@ss 5.1 | 27140702 |
| eCl@ss 6.0 | 27140702 |
| eCl@ss 7.0 | 27140702 |
| eCl@ss 8.0 | 27140702 |

ETIM

| ETIM 3.0 | EC000046 |
|----------|----------|
| ETIM 4.0 | EC000046 |
| ETIM 5.0 | EC000046 |

UNSPSC

| UNSPSC 6.01 | 30212109 |
|---------------|----------|
| UNSPSC 7.0901 | 27121703 |
| UNSPSC 11 | 27121703 |
| UNSPSC 12.01 | 27121703 |
| UNSPSC 13.2 | 27121703 |

Accessories

Accessories

Universal tools



Cable tie - WT-HT HF 3,6X200 BK - 3240785

Accessories

Cable tie tool - UNIFOX-CT 4,8 - 1212475



Cable binder pliers, for plastic cable binders with a width of 2.2 - 4.8 mm, for a material thickness of up to 1.6 mm

Cable tie tool - UNIFOX-CT 4,8P - 1212609



Cable binder pliers, for plastic cable binders with a width of 2.2 - 4.8 mm, for a material thickness of up to 1.6 mm

Phoenix Contact 2016 $\ensuremath{\mathbb{C}}$ - all rights reserved http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 3240785