

Oct.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
	OPERATING&STORAGE HUMIDTY RANGE	85 % MAX	APPLICABLE CABLE	CABLE DIAMETER : $\phi 9.6 \pm 0.5$
<b>SPECIFICATIONS</b>				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
<b>CONSTRUCTION</b>				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
				
REMARK		APPROVED	A0. SUZUKI	09. 10. 05
		CHECKED	KN. ICHIKAWA	09. 10. 02
		DESIGNED	TU. TANIGUCHI	09. 10. 02
Unless otherwise specified, refer to JIS C 5402.		DRAWN	TU. TANIGUCHI	09. 10. 02
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-126660-00	
<b>HRS</b>	SPECIFICATION SHEET	PART NO.	DH-51-CMB (9. 6)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0034-3-00	 1/