

## RF Attenuator 6810.26.A

### Description

Standard Attenuator, Low Power



### Product Configuration

Connector (side 1 / side 2) TNC plug (male) / TNC jack (female)  
 Interface Standards IEC 60169-17\_MIL-STD-348A/313\_CECC 22200

### Technical Data

#### Electrical Data

Nominal impedance	50 Ω			
Nominal attenuation	10 dB			
Frequency range	DC to 12.4 GHz			
Frequency sub range (GHz)	DC to 4	4 to 8	8 to 11	11 to 12.4
Attenuation deviation (±dB)	0.3	0.5	0.8	0.8
VSWR max.	1.1	1.2	1.3	1.4
Power rating	1 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient temperature. 500 Watt peak power, 5 μs pulse, 0.05 % duty cycle			

#### Mechanical Data

Weight 0.029 kg

#### Environmental Data

Operating temperature -55 °C to 130 °C  
 2011/65/EU (RoHS) compliant

#### Material Data

Piece Part (side 1)	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Piece Part (side2)	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

### Related Documents

Outline drawing DOU-00005277

### Ordering Information

Single packaging 6810.26.A

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[6810.26.A](#)