

Part Number : 330123001

Series Number : 33012 Product Category : Crimp Terminals

Documents & Resources

Drawings

Drawing 330123001_sd.pdf Packaging Design Drawing 313025040-000.pdf Packaging Design Drawing 313025040-000.pdf

Specifications

Application Specification AS-33012-002-001.pdf Application Specification 330120000-AS-KR-000.pdf Test Summary TS-33012-002-001.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Compliant with Exemption 44; 34; 33 |
|--------------------|--|
| China RoHS | (|
| EU ELV | Compliant per 2000/53/EC |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS

- REACH SVHC

- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D

- Molex Product Compliance Declaration

Product Description : MX150 Female Terminal for Mat-Sealed Connectors, Tin Plating, 16-14 AWG, Left Reel Payoff Status : Active - IEC-62474

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| _ | |
|----------------|---|
| Status | Active |
| Category | Crimp Terminals |
| Series | 33012 |
| Description | MX150 Female Terminal for Mat- Sealed Connectors, Tin Plating, 16- 14 AWG, Left Reel Payoff |
| Application | Power, Wire-to-Board, Wire-to- Wire, Automotive |
| Comments | Left Reel Payoff, Small Polarization Rib |
| Product Family | MX150 Sealed and Unsealed Connector System |
| Product Name | MX150 |
| UPC | 822350084284 |

Electrical

| Current - Maximum per Contact | Contact Molex |
|-------------------------------|---------------|
| Voltage - Maximum | 14V DC |

Physical

| Durability (mating cycles max) | 25 |
|--------------------------------|------------------------------|
| Gender | Female |
| Grip Code | 14 |
| Material - Metal | High Performance Alloy (HPA) |
| Material - Plating Mating | Tin |
| Material - Plating Termination | Tin |
| Net Weight | 0.391/g |
| Packaging Type | Reel |
| Plating min - Mating | 0.508µm |
| Plating min - Termination | 0.508µm |
| Termination Interface Style | Crimp or Compression |

| Wire Insulation Diameter | 2.70mm max. |
|---------------------------|-------------|
| Wire Size (AWG) | 14, 16 |
| Wire Size mm ² | 1.25-2.00 |

Solder Process Data

| | N1/A |
|------------------------------|------|
| Lead-Free Process Capability | N/A |

Use with Part(s)

| Description | Part Number |
|--|--------------|
| MX150 Mat-Sealed Single Row Female Connector Assemblies | <u>33471</u> |
| MX150 Mat-Sealed Dual Row Female Connector Assemblies | <u>33472</u> |

Application Tooling

Global

| Description | Part Number |
|---|------------------|
| Extraction Toolkit for MX150 Connectors | 2002220700 |
| FA2 Mechanical Feed Crimp Applicator for MX150 Mat Seal/Unsealed Receptacle Terminals, 14 AWG,16 AWG, 1.25mm ² and 1.50mm ² | <u>638082300</u> |
| FA2 Pneumatic Feed Applicator for MX150 Mat Seal/Unsealed Receptacle Terminals, 14 AWG, 16 AWG, 1.25mm ² and 1.50mm ² | <u>638082310</u> |
| FA2 Pneumatic Feed Crimp Applicator for MX150 Mat Seal Terminals, 14 AWG, 1.25mm ² and 2.00mm ² Wire | <u>638088110</u> |
| PremiumGrade Hand Crimp Tool for MX150 Female Terminals, 16-14 AWG | <u>638115900</u> |
| PremiumGrade Hand Crimp Tool for MX150 Female Terminals for 1.00mm ² and 1.50mm ² Metric Wires | <u>638116100</u> |
| Extraction Tool for MX150L, MX150, PT Bulb Socket, iGrid, SPOX, and Wire-to-Motor Terminals | <u>638131500</u> |

| FineAdjust Applicator for SRC Connector using MX150 Receptacle Terminals, 1.50mm ² wires | <u>639040600</u> |
|---|------------------|
| FineAdjust Applicator for SRC Connector using MX150 Receptacle Terminals, 2.00mm ² wires | <u>639040700</u> |
| ServiceGrade Hand Crimp Tool for MX150 Crimp Terminals, 22-14 AWG | <u>640160133</u> |

This document was generated on Sep 16, 2024