



| JKL LAMP PART NO. | COLOR WHITE 6900°KELVIN | STARTING CIRCUIT VOLTAGE VS (Vrms) | OPERATING LAMP VOLTAGE VL (Vrms) | OPERATING LAMP CURRENT IL (mArms) | BRIGHTNESS (CANDELA/m ²) | *RATED LIFE (HRS) MINIMUM |
|-------------------|-------------------------------|--|--|---|---|---------------------------------|
| BF20125-28B | x = .325 y = .295 | 700 @ 0°C | 280 | 5 | 38,000 TYP. | 20,000 |

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

| | | | | | | | | |
|---|--|--|---|--|---|--|--------------------------|--|
| | | | METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0 | | JKL COMPONENTS CORPORATION | | | |
| | | | | | TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP | | | |
| DRAWN BY L. WENGSTROM | | | APPVD BY L.R. | | DATE 7/30/09 | | SIZE A | |
| FSCM NO. 55335 | | | DRAWING NO. BF20125-28B | | | | | |
| - CAD DRAWING - MANUAL REVISIONS NOT PERMITTED | | | SCALE NONE | | RELEASED DATE 4/22/04 | | REVISION DATE 7/30/09 | |
| REV. NO. | | | DESCRIPTION/ECO NUMBER | | APPVD DATE | | REV. NO. A | |
| A | | | RATED LIFE HRS MINIMUM 7/30/09 | | RELEASE & CANCEL P-0404-14 4/22/04 | | SHEET 1 OF 1 | |