

RAYCHEM | RAYCHEM ATUM


TE Internal #: NB10892001

Black, 3:1, Dual Wall Tubing, Shrinks To 1.5 mm [.059 in], Irradiated Modified Polyolefin, 4.5 mm [.177 in] Inner Diameter, RAYCHEM ATUM

View on TE.com >



Heat Shrink Tubing > ATUM 3:1 Heat Shrink Tubing



Primary Product Color: Black

Wall Type: **Dual Wall**

Expanded Inside Diameter (Min): 4.5 mm [.177 in]
Recovered Inside Diameter (Max): 1.5 mm [.059 in]

Shrink Ratio: 3:1

All ATUM 3:1 Heat Shrink Tubing (135)

Recovered Wall Thickness (Tolerance)

Features

Product Type Features

Wall Type	Dual Wall
Electrical Characteristics	
Operating Voltage (Max)	.6 kV
Body Features	
Fluid Type	Aviation Fuel, Chemicals/Solvents, De-Icing Fluid, Diesel Fuel, Hydraulic Fluid, Lubricating Oil
Primary Product Color	Black
Shrink Ratio	3:1
Primary Product Material	Irradiated Modified Polyolefin
Flexibility	Semi-Flexible
Dimensions	

.3 mm[.012 in]



Recovered Wall Thickness (Nominal)	1 mm[.039 in]
Product Length	1220 mm[48.031 in]
Expanded Inside Diameter (Min)	4.5 mm[.177 in]
Recovered Inside Diameter (Max)	1.5 mm[.059 in]
Tubing Size Range	1.5 – 4.5 mm[.059 – .177 in]
Usage Conditions	
Shrink Temperature (Min)	80 °C
Tubing Flammability Type	Flame-Retardant
Operating Temperature Range	-55 – 110 °C
Recovery Temperature	110 °C
Operation/Application	
Mechanical Resistance	Fluids, Mechanical Damage, Strain Relief
Product Availability	
Applicable Region	Global
Packaging Features	
Packaging Method	Bag & Box
Other	
Meets Low Outgassing Requirements	No

Product Compliance

Product Source

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: DBMC (1.54% in Component Part) Article Safe Usage Statements: Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.

Czech Republic



Solder Process Capability

Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | RAYCHEM ATUM



Customers Also Bought



















Documents

Product Drawings

ATUM-4.5/1.5-0-STK

English

Datasheets & Catalog Pages

ATUM Tubing

English

Product Specifications

Application Specification

English