

Main

Range	TeSys
Device short name	LA4D
Product or Component Type	Suppressor module
Product compatibility	4P LP1D80 3P LC1D80...D95 4P LP1D40...D65

Complementary

Mounting Location	Top
Mounting Mode	By screws
Suppressor technology	Bidirectional peak limiting diode
[Uc] control circuit voltage	72 V DC
Maximum peak voltage	2 Uc
Net Weight	0.040 lb(US) (0.018 kg)

Environment

Standards	IEC 60947-5-1 EN 60947-5-1 CSA C22.2 No 60947-5-1 UL 60947-5-1 GB/T 14048.5
Product Certifications	UL[RETURN]CSA
IP degree of protection	IP2XIEC 60529
Ambient Air Temperature for Operation	-13...131 °F (-25...55 °C)
Ambient Air Temperature for Storage	-40...176 °F (-40...80 °C)

Ordering and shipping details

Category	US10I1222341
Discount Schedule	0I12
GTIN	3389110336511
Returnability	No
Country of origin	BG

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.05 in (5.200 cm)
Package 1 Width	1.73 in (4.400 cm)
Package 1 Length	1.10 in (2.800 cm)
Package 1 Weight	0.600 oz (17.000 g)
Unit Type of Package 2	S01
Number of Units in Package 2	78
Package 2 Height	5.91 in (15.000 cm)

Package 2 Width	5.91 in (15.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	3.303 lb(US) (1.498 kg)

Offer Sustainability

Packaging without single use plastic	No
Packaging made with recycled cardboard	No
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	No
Carbon footprint (kg CO2 eq, Total Life cycle)	1

Contractual warranty

Warranty	18 months
----------	-----------