

REV. 1
DCO 142087


COIL: @ 25°C
 RESISTANCE _____ 850 OHMS ± 10%
 NOMINAL VOLTAGE _____ 12.0 VDC
 MUST OPERATE _____ 7.0 VDC

 MUST RELEASE _____ 4.0 VDC MAX, 0.64 VDC MIN.

ENVIRONMENT:
 VIBRATION _____ 10 _____ CPS TO _____ 3000 _____ CPS @ _____ 30 _____ g's
 SHOCK _____ 75 _____ g's _____ 6 _____ MS. DURATION
 TEMPERATURE _____ -65 _____ °C TO _____ +125 _____ °C

NOTES: _____ OPERATE TIME 4.0 MS MAX
 _____ RELEASE TIME 2.0 MS MAX
 _____ CONTACT BOUNCE 1.5 MS MAX

CUSTOMER DATA SHEET



TERMINAL VIEW

CONTACT RATING: _____ LOW LEVEL TO _____
 _____ 1A 28 VDC RESISTIVE 100,000 _____
 _____ OPERATIONS _____

DR. R.B. 10/3/95 CK *Levan C* 6/2/00



CUST. _____ OPL _____
 CUST. NO. M39016/11-043L REV. _____

'JMS' RELAY

JMSC-12XLS

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JM5C-12XLS](#)