### **EPC.00.250.NTN**





# **Summary**

#### Request a quote

Catalog		
Nb of contacts Coax	1	
Socket / Receptacle	Socket / Receptacle - Free	
Locking system	Push-pull	
Series	00 - NIM-CAMAC	

## **Technical details**

#### **Electrical Configuration**

Nb of contacts Coax	1	
R (max)	6.1 mOhm	
Insert configuration value	0.25 - 1 Coax (50 Ohm)	
Insulator	T: PTFE	
Rated current	4 A	
Impedance	50 Ohm	
VSWR	1.09 + 0.11 * f/GHz	
Vtest	2100 V (AC), 3000 V (DC)	
Contact Type	Coaxial 50 Ohm (Printed Circuit Board)	
Test voltage	2.1 kV (rms)	
Contact Dia.	0.7 mm (0.028in)	
Form & Material		
Shell style / Model id	EPC - Straight receptacle for printed circuit with clearance under the body	
Socket / Receptacle	Free	
Housing material	Brass (nickel plated [SAE AMS QQ N 290]) shell, collet nut, latch sleeve and mid pieces	
Locking system	Push-pull	
Keying	Circular, female	
Weight	3.3 g	
Environment		
Environmental sealing (IP rating)	IP50	
Temperature range	-55°C / +260°C	
F ret (min)	100 N	
Salt Spray Corrosion	>144 hr	

# **Drawings**





### **Dimensions**

	A	L
mm.	7	14
in.	0.28	0.55