Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Commercial Status	Commercialised
Range of product	OsiSense XCC
Encoder type	Multiturn absolute encoder fieldbus
Encoder name	XCC
Product specific application	-
Diameter	2.28 in (58 mm)
Bus type	Profibus DP 3.062 V1.1. IEC 61158, EN 50170 class 2, IEC 61784, EN 50254
Shaft diameter	0.59 in (15 mm)
Shaft type	Hollow
Resolution	4096 turns/8192 points
Electrical connection	3 cable glands Pg 9 radial external supply
Type of output stage	PROFIBUS-DP 25-bit
[Us] rated supply voltage	24 V DC
Transmission rate	9.6 kbit/s12000 kbit/s
Enclosure material	Aluminium

Complementary

Shaft tolerance	F7
Supply voltage limits	1030 V DC
Maximum revolution speed	6000 rpm
Shaft moment of inertia	0.01 lb.in² (30 g.cm²)
Torque value	0.03 lbf.in (0.003 N.m)
Maximum load	11 daN radial
Output frequency	800 kHz
Current consumption	0100 mA no-load
Protection type	Reverse polarity protection Voltage peaks protection
Status LED	1 LED red error 1 LED green status
Surge withstand	0.5 kV level 1 IEC 61000-4-5
Base material	Aluminium
Shaft material	Stainless steel
Type of ball bearings	6803ZZ
Product weight	1.26 lb(US) (0.57 kg)

Environment

Product certifications	DIN VDE 0160	
	PNO	
	Schneider Electric interoperability standards	
Marking	CE	
Ambient air temperature for operation	-40185 °F (-4085 °C)	
Ambient air temperature for storage	-40185 °F (-4085 °C)	
IP degree of protection	IP64 IEC 60529	
Vibration resistance	10 gn (102000 Hz) IEC 60068-2-6	
Shock resistance	100 gn (6 ms) IEC 60068-2-27	

Resistance to electrostatic discharge	4 kV air discharge level 2 IEC 61000-4-2 2 kV contact discharge level 2 IEC 61000-4-2	
Resistance to electromagnetic fields	9.14 V/yd (10 V/m) level 3 IEC 61000-4-3	·
Resistance to fast transients	2 kV power ports level 3 IEC 61000-4-4 1 kV signal ports level 3 IEC 61000-4-4	

Ordering and shipping details

Category	21581 - ENCODERS, XCC	
Discount Schedule	DS2	
GTIN	003389119056267	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.74	
Product availability	Non-Stock - Not normally stocked in distribution facility	
Returnability	N	-
Country of origin	FR	

Offer Sustainability

|--|

Contractual warranty

	nonths
--	--------



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XCC3515CV84FBN