





## GLASS PASSIVATED SURFACE MOUNT BRIDGE RECTIFIERS

### Features

- ◆ Glass Passivated Chip Junction
- ◆ Reverse Voltage - 1000 V
- ◆ Forward Current- 5.0 A
- ◆ Fast reverse recovery time
- ◆ Designed for Surface Mount Application

**TTF**
**RoHS**  
COMPLIANT


Dimensions in inches and (millimeters)

### Mechanical Data

Case : JEDEC TTF molded plastic body

Terminals : Solderable per MIL-STD-750, Method 2026A

Polarity : Polarity symbol marking on body Mounting

Position : Any

Weight : 0.0163 ounce, 0.461 grams

### **Maximum Ratings And Electrical Characteristics (TA=25°C unless otherwise specified)**

Single phase half-wave 60Hz,resistive or inductive load,for capacitive load current derate by 20% .

PARAMETER	SYMBOL	TTR5MF		Units
Maximum Recurrent Peak Reverse Voltage	V <sub>RRM</sub>	1000		V
Maximum RMS voltage	V <sub>RMS</sub>	700		V
Maximum DC Blocking Voltage	V <sub>DC</sub>	1000		V
Average Rectified Output Current at T <sub>c</sub> = 100°C	I <sub>o</sub>	5.0		A
Peak Forward Surge Current,8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I <sub>FSM</sub>	180		A
I <sup>2</sup> t Rating for Fusing	I <sup>2</sup> t	134.46		A <sup>2</sup> S
Typical Thermal Resistance <sup>(1)</sup>	R <sub>θJA</sub> R <sub>θJC</sub> R <sub>θJL</sub>	60 6 14		°C/W
Operating and Storage Temperature Range	T <sub>j</sub> , T <sub>stg</sub>	-55 ~ +150		°C

### **Maximum Ratings And Electrical Characteristics (TA=25°C unless otherwise specified)**


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	Units
Instantaneous forward voltage	V <sub>F</sub>	I <sub>F</sub> = 5 A T <sub>J</sub> =25°C	-	-	1.1	V
Reverse current at DC blocking voltage	I <sub>R</sub>	T <sub>J</sub> =25°C T <sub>J</sub> =125°C	-	-	5 200	uA
Maximum Reverse Recovery Time	t <sub>rr</sub>	Measured with I <sub>F</sub> = 0.5 A, I <sub>R</sub> = 1 A, I = 0.25 A .	-	-	500	ns
Typical Junction Capacitance	C <sub>j</sub>	f=1MHz,VR=4V DC T <sub>J</sub> =25°C	-	60	-	pF

Note: 1. Measured at 1MHz and applied reverse voltage of 4 V D.C.


2. P.C.B. mounted with 4×1.5"×1.5" ( 3.81×3.81 cm ) copper pad areas.

## Typical Characteristics


**Fig.1 Average Rectified Output Current Derating Curve**




**Fig.2 Typical Reverse Characteristics**




**Fig.3 Typical Instantaneous Forward Characteristics**




**Fig.4 Typical Junction Capacitance**



**Fig.5 Maximum Non-Repetitive Peak Forward Surge Current**




**Fig.6- Typical Transient Thermal Impedance**



The curve above is for reference only.

## Suggested Pad Layout

**Note:**

1. Controlling dimension: in/millimeters.
2. General tolerance:  $\pm 0.05\text{mm}$ .
3. The pad layout is for reference purposes only.

Unit:  $\frac{\text{mm}}{(\text{mil})}$