


COIL: @ 25°C
 RESISTANCE 2000 OHMS ±10%
 NOMINAL VOLTAGE 26.5 VDC
 MUST OPERATE 14.2 VDC
 MUST RELEASE 8.0 VDC MAX., 1.37 VDC MIN.

ENVIRONMENT:
 VIBRATION 10 Hz TO 3000 Hz @ 30 g's
 SHOCK 75 g's 6 MS. DURATION
 TEMPERATURE -65 °C TO +125 °C

NOTES:
 OPERATE TIME 2.0 MS MAX.
 RELEASE TIME 2.0 MS MAX.
 CONTACT STABILIZATION TIME 2.0 MS MAX.

CUSTOMER DATA SHEET



TERMINAL VIEW

CONTACT RATING: LOW LEVEL TO 1A
 28 VDC RESISTIVE 100,000 OPERATIONS

DR. B.D. 21MAY03

CK. [Signature] 5/21/03

CII Technologies
 advanced control electronic solutions

CUST. GPL
 CUST. NO. M39016/7-036M REV.

"J1MA" RELAY

J1MAC-26XMS

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[J1MAC-26XMS](#)