SMD LED 0805, Super-Red

multicomp

RoHS

Compliant



Specifications:

Dice material	: (
Emitted colour	: 8
Epoxy colour	: \
Peak wavelength	: 6
Viewing angle	: 1
Luminous intensity (IV)	: '

- : GaAlAs
- : Super Red
- : Water Clear
- 660nm
- : 140°
- : 17mcd

Absolute Maximum Ratings (T_a = 25°C)

Reverse Voltage	5V		
Reverse Current	10µA (V _R = 5V)		
Operating Temperature Range	-40°C to +85°C		
Storage Temperature Range	-40°C to +100°C		
Lead Soldering Temperature Range 1.6mm (1/16 inch) from body			

Electrical/Optical Characteristics at T_a = 25°C

Parameter	Symbol	Minimum	Typical	Maximum	Unit	Test
Luminous Intensity	IV	14	17	20	mcd	IF = 20mA
Viewing Angle	20 1/2	-	140	-	degrees	1F – 2011A
Peak Emission Wavelength	λP	-	660	-		-
Dominant Wavelength	λD	-	643	-	nm	-
Spectral Line Half-Width	Δλ	-	20	-		-
Forward Voltage	VF	1.5	1.85	2.4	V	IF = 20mA
Power Dissipation	Pd	-	-	100	-	-
Peak Forward Current (Duty 1/10 at 1KHz)	IF (Peak)	-	-	120	-	-
Recommended Operating Current	IF (Rec)	-	20	-	mA	-


www.element14.com www.farnell.com www.newark.com



SMD LED 0805, Super-Red



Super Red (GaAlAs) λP = 660nm)




www.element14.com www.farnell.com www.newark.com



11/10/12 V1.0

SMD LED 0805, Super-Red





Part Number Table

Description	Part Number	
LED, SMD, 0805, Super-Red	MCL-S270SRC	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheets hould check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com

