

# Cable Gland *Industrial Straight-Through - PVDF*

## Material:

- Body: Polyvinylidene fluoride
- Seal: Santoprene
- ECA clamping ring: Polycarbonate

## Characteristics:

- Metric thread
- ECA clamping ring

Temperature Range
-40 to 120°C (-40 to 248°F)

## Technical properties:

- No halogen
- Strain relief through clamping ring
- Gas tight and watertight
- Completely twist protected
- Combinable with various sealing inserts
- Chemical resistant

## Applications:

- Machines and devices
- Measuring and control engineering
- Plant installations
- Food sector




## Metric Thread

### ECA

Outer thread	Clamping range mm	Cat. No.	Std. Pk.
M 16 x 1.5	5-8	5330016	50
M 20 x 1.5/13	8-12	5330020	50
M 20 x 1.5/16	10-14	5330021	50
M 25 x 1.5	11.5-18	5330025	20
M 32 x 1.5	15-24	5330032	20

### Dimensions

Thread Size	H mm	E mm	L mm	ØC mm	ØP mm	ØM mm
M 16x1.5	19	15	39	8.5	9	16
M 20x1.5/13	24	15	42	12.5	13.5	20
M 20x1.5/16	27	15	45	14.5	15	20
M 25x1.5	33	15	48	18.5	19	25
M 32x1.5	42	15	58	25	25	32



Locknuts and seal rings sold separately, see pages 24 and 35.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Altech:](#)

[4221117](#) [4221095](#) [4221732](#) [4221427](#) [4221750](#) [4221733](#) [4221720](#) [4221362](#) [4221740](#) [4221721](#) [4221079](#)  
[4221290](#) [4221214](#) [4221717](#) [4221168](#) [4221716](#) [4221486](#) [4221714](#) [4221133](#) [4221725](#) [4221760](#) [4221726](#)