W51-A151A1-7 - ACTIVE

TE Internal #: 1-1423673-6 Thermal, Trip-Free - Switchable, Black, Operating Voltage 125 VAC, Operating Voltage 50 VDC, 7A Current Rating, 1 Pole, Circuit Breakers

View on TE.com >



Relays & Contactors > Circuit Breakers



Circuit Breaker Type: Thermal

Circuit Function: Trip-Free - Switchable

Illuminated: Without

Actuator Color: Black

Operating Voltage: 125 VAC

Features

Product Type Features

Circuit Breaker Style	Angular Button
Illumination Type	No Light
Actuator Type	Rocker
Circuit Breaker Type	Thermal

Illuminated	Without			
Configuration Features				
Panel Cutout Size	28.5 x 13.5 mm[1.122 x .531 in]			
Circuit Function	Trip-Free - Switchable			
Number of Poles	1			
Electrical Characteristics				
Operating Voltage	50 VDC			
Current Rating	7 A			
Interrupt Capacity	1000A @ 250VAC/50VDC			
Body Features				
Actuator Color	Black			
Contact Features				
Trip Time at 200%	4 – 40 seconds			
Termination Features				

W51-A151A1-7

Thermal, Trip-Free - Switchable, Black, Operating Voltage 125 VAC, Operating Voltage 50 VDC, 7A Current Rating, 1 Pole, Circuit Breakers



Terminal Configuration	6.35 [.25] Straight Quick Connect Tab				
Mechanical Attachment					
Mounting Options	Snaps Into 1.122 x .531 (28.5 x 13.5) Panel Cutout				
Dimensions					
Panel Thickness (Recommended)	.75 – 3 mm[.03 – .118 in]				
Identification Marking					
Stamped Marking Type	RESET/OFF Printed				
Product Compliance For compliance documentation, visit the product page on TE.com>					
EU RoHS Directive 2011/65/EU	Compliant with Exemptions				
EU ELV Directive 2000/53/EC	Not Compliant				
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold				
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold:				

Halogen Content

Solder Process Capability

Cd (1.55% in Component Part) Article Safe Usage Statements:

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

W51-A151A1-7

Thermal, Trip-Free - Switchable, Black, Operating Voltage 125 VAC, Operating Voltage 50 VDC, 7A Current Rating, 1 Pole, Circuit Breakers





Customers Also Bought



TE Part #925324-2 FF 250 PLUG HSG 1P NYLON CLEAR	TE Part #5-160558-2 FF 250 REC 0.5-1.5MM2 TPBR	TE Part #1-826656-0 10P AMPMODU II STIFT LEI	TE Part #3-2176340-7 CRGCQ 0603 1M0 5%
TE			
TE Part #5-160491-2 187 FASTON REC 18-14 AWG TPBR	TE Part #9-2176366-1 RQ 0603 3K74 0.1% 10PPM 1K RL		

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1423673-6_E.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1423673-6_E.3d_igs.zip

English

W51-A151A1-7

Thermal, Trip-Free - Switchable, Black, Operating Voltage 125 VAC, Operating Voltage 50 VDC, 7A Current Rating, 1 Pole, Circuit Breakers



Customer View Model

ENG_CVM_CVM_1-1423673-6_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

W51 Rocker-Actuated Thermal Circuit Breaker/Power Switch With Optional Indicator Lamp

English

Agency Approvals CCC Certificate

English