



SITOP PSU8200/3AC/48VDC/10A

SITOP PSU8200 48 V/10 A
 Stabilized power supply input: 3
 AC 400-500 V output: 48 V
 DC/10 A

Input	
Input	3-phase AC
Rated voltage value V_{in} rated	400 ... 500 V
Voltage range AC	320 ... 575 V
Wide-range input	Yes
Mains buffering	at $V_{in} = 400$ V
Mains buffering at I_{out} rated, min.	15 ms; at $V_{in} = 400$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
input current	
• at rated input voltage 400 V	1.2 A
• at rated input voltage 500 V	1 A
Switch-on current limiting (+25 °C), max.	16 A
I^2t , max.	0.8 A ² ·s
Built-in incoming fuse	none
Protection in the mains power input (IEC 898)	Required: 3-pole connected miniature circuit breaker 6 ... 16 A characteristic C or circuit breaker 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489)
Output	
Output	Controlled, isolated DC voltage
Rated voltage V_{out} DC	48 V
Total tolerance, static \pm	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.2 %
Residual ripple peak-peak, max.	100 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	200 mV
Adjustment range	42 ... 56 V
product function output voltage adjustable	Yes
Output voltage setting	via potentiometer; max. 480 W
Status display	Green LED for 48 V OK
Signaling	Relay contact (NO contact, rating 60 V DC/ 0.3 A) for 48 V OK
On/off behavior	No overshoot of V_{out} (soft start)
Startup delay, max.	2.5 s
voltage increase time of the output voltage maximum	500 ms

Rated current value I _{out} rated	10 A
Current range	0 ... 10 A
• Note	+60 ... +70 °C: Derating 2%/K
supplied active power typical	480 W
short-term overload current	
• at short-circuit during operation typical	30 A
duration of overloading capability for excess current	
• at short-circuit during operation	25 ms
constant overload current	
• on short-circuiting during the start-up typical	11 A
Parallel switching for enhanced performance	Yes; switchable characteristic
Numbers of parallel switchable units for enhanced performance	2
Efficiency	
Efficiency at V _{out} rated, I _{out} rated, approx.	94 %
Power loss at V _{out} rated, I _{out} rated, approx.	31 W
Closed-loop control	
Dynamic mains compensation (V _{in} rated ±15 %), max.	0.1 %
Dynamic load smoothing (I _{out} : 50/100/50 %), U _{out} ± typ.	1 %
Load step setting time 50 to 100%, typ.	0.2 ms
Load step setting time 100 to 50%, typ.	0.2 ms
Dynamic load smoothing (I _{out} : 10/90/10 %), U _{out} ± typ.	2 %
Load step setting time 10 to 90%, typ.	0.2 ms
Load step setting time 90 to 10%, typ.	0.2 ms
setting time maximum	10 ms
Protection and monitoring	
Output overvoltage protection	< 60 V
Current limitation, typ.	11 A
property of the output short-circuit proof	Yes
Short-circuit protection	Alternatively, constant current characteristic approx. 11 A or latching shutdown
enduring short circuit current RMS value	
• typical	11 A
overcurrent overload capability in normal operation	overload capability 150 % I _{out} rated up to 5 s/min
Overload/short-circuit indicator	LED yellow for "overload", LED red for "latching shutdown"
Safety	
Primary/secondary isolation	Yes
galvanic isolation	Safety extra low output voltage V _{out} according to EN 60950-1
Protection class	Class I
leakage current	
• maximum	3.5 mA
• typical	0.9 mA
Degree of protection (EN 60529)	IP20
Approvals	
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
Explosion protection	IECEX Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nA nC IIC T4; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T4
certificate of suitability NEC Class 2	No
FM approval	-
CB approval	Yes
Marine approval	ABS, DNV GL
EMC	
Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

environmental conditions		
ambient temperature	-25 ... +70 °C with natural convection	
<ul style="list-style-type: none"> • during operation — Note • during transport • during storage 		
Humidity class according to EN 60721		Climate class 3K3, 5 ... 95% no condensation
Mechanics		
Connection technology	screw-type terminals	
Connections	L1, L2, L3, PE: 1 screw terminal each for 0.2 ... 4 mm ² single-core/finely stranded +, -: 2 screw terminals each for 0.2 ... 4 mm ² 13, 14 (alarm signal): 1 screw terminal each for 0.14 ... 1.5 mm ² ; 15, 16 (Remote): 1 screw terminal each for 0.14 ... 1.5 mm ²	
<ul style="list-style-type: none"> • Supply input • Output • Auxiliary 		
width of the enclosure		70 mm
height of the enclosure		125 mm
depth of the enclosure	125 mm	
required spacing	50 mm 50 mm 0 mm 0 mm	
<ul style="list-style-type: none"> • top • bottom • left • right 		
Weight, approx.		1.2 kg
product feature of the enclosure housing can be lined up		Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15	
mechanical accessories	Device identification label 20 mm × 7 mm, TI-grey 3RT2900-1SB20	
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)	

