

RJI RJ45 PN plug Cat5, 4p IDC straight



•	
Part number	09 45 151 1120
Specification	RJI RJ45 PN plug Cat5, 4p IDC straight
HARTING eCatalogue	https://b2b.harting.com/09451511120

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	HARTING RJ Industrial [®]
Element	Cable connector
Specification	PROFINET Straight
Version	
Termination method	IDC termination
Shielding	Fully shielded, 360° shielding contact
Number of contacts	4
Technical characteristics	
Conductor cross-section	0.1 0.32 mm²
Conductor cross-section [AWG]	AWG 27/7 AWG 22/7 Stranded AWG 27/1 AWG 22/1 Solid
Wire outer diameter	1.6 mm
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s
Limiting temperature	-40 +70 °C
Relative humidity	95 % Non-condensing (operation)
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP20

Page 1 / 2 | Creation date 2024-06-22 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Technical characteristics

Cable diameter	4.5 9 mm
Material properties	
Material (hood/housing)	Polyamide (PA)
Colour (hood/housing)	Black
Material flammability class acc. to UL 94	V-0
·	
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R26

Specifications and approvals

Specifications	EN 45545-2
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079
Approvals	DNV GL
PROFINET	Yes

Commercial data

Packaging size	10
Net weight	24.5 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140059351
ETIM	EC002636
eCl@ss	27440114 Rectangular connector (for field assembly)

Page 2 / 2 | Creation date 2024-06-22 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com