# KRPA-14DG-48 ACTIVE

#### Potter & Brumfield | Potter & Brumfield KRPA

TE Internal #: 8-1393104-5

General Purpose Power Relay, Monostable, 1.3 W Coil, 1800 ohm Coil Resistance, UL Coil Insulation Class B, Potter & Brumfield

KRPA, Power Relays

View on TE.com >



Relays & Contactors > Relays > Power Relays



Relay Type: General Purpose Power Relay

Coil Magnetic System: Monostable

Coil Power Rating DC: 1.3 W

Coil Resistance: 1800  $\Omega$ 

Coil Special Features: UL Coil Insulation Class B

#### **Features**

#### **Product Type Features**

Relay Type	General Purpose Power Relay
Configuration Features	
Coil Special Features	UL Coil Insulation Class B
Contact Arrangement	3 Form C 3PDT-CO
Contact Number of Poles	3
Electrical Characteristics	
Insulation Initial Dielectric Between Open Contacts	1000 Vrms
Contact Limiting Making Current	10 A
Contact Limiting Short-Time Current	10 A
Contact Limiting Continuous Current	10 A
Insulation Initial Dielectric Between Adjacent Contacts	1000 Vrms
Insulation Initial Dielectric Between Contacts & Coil	1000 Vrms
Insulation Initial Resistance	1000 ΜΩ
Contact Limiting Breaking Current	10 A
Coil Power Rating DC	1.3 W
Coil Resistance	1800 Ω
Coil Voltage Rating	48 VDC
Contact Current Rating	10 A



Contact Switching Load (Min)	300mA @ 12V
Contact Voltage Rating	240 VAC
Body Features	
Product Weight	85 g[2.988 oz]
Contact Features	
Contact Material	AgCdO
Termination Features	
Relay Connection Type	Plug-In
Mechanical Attachment	
Product Mounting Feature Type	Mounting Studs
Product Mount Type	Socket
Dimensions	
Product Width	35.71 mm[1.4 in]
Product Length	35.71 mm[1.4 in]
Product Height	50.8 mm[2 in]
Usage Conditions	
Environmental Category of Protection	RTI
Environmental Ambient Temperature (Max)	70 °C[158 °F]
Operating Temperature Range	-45 – 70 °C
Operation/Application	
Current Type	DC
Coil Magnetic System	Monostable
Packaging Features	
Packaging Method	Package
Other	
Length Class (Mechanical)	35 – 40 mm
Environmental Ambient Temperature Class	50 – 70 °C
Height Class (Mechanical)	50 – 60 mm
Coil Power Rating Class	1 – 1.5 W
Width Class (Mechanical)	30 – 40 mm
Contact Current Class	16 A



#### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUL 2021 (219) SVHC > Threshold: Cadmium oxide (10% in Component Part) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

### **Compatible Parts**





Also in the Series | Potter & Brumfield KRPA









## Customers Also Bought





TE Part #34123 TERMINAL,SOLIS R 16-14 10

















### **Documents**

**CAD Files** 

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_8-1393104-5\_D.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_8-1393104-5\_D.3d\_igs.zip

General Purpose Power Relay, Monostable, 1.3 W Coil, 1800 ohm Coil Resistance, UL Coil Insulation Class B, Potter & Brumfield KRPA, Power Relays



English

**Customer View Model** 

ENG\_CVM\_CVM\_8-1393104-5\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

KRPA, KRP, KA, KR 5 to 10 Amp General Purpose Relay

English

**KR Sockets & Accessories** 

English

**Product Specifications** 

**Definitions General Purpose Relays** 

English

**Agency Approvals** 

UL

English