

SP3-90-6 GAS DISCHARGE SURGE PROTECTORS



GAS DISCHARGE SURGE PROTECTORS

DC to 3000 MHz Operation

The surge protectors offered by Laird Technologies are an integral part of any antenna installation in protecting sensitive equipment from surges caused by lightning. The ultra-fast gas discharge tube design gives quick response to power surges and dumps the excess power safely to the ground. A ground lug terminal is supplied to provide superior grounding. The units have the ability to withstand multiple lightning strikes. The SP3-90-6 passes DC voltage, so it is also suitable for systems that pass DC power through the coax, such as remote amplifiers.

FEATURES **V**RoHS

- Ultra fast gas discharge
- Multiple strike 6 KA discharge
- 0.4 db max insertion loss

APPLICATIONS

- Lightning protection for antenna systems
- 900 MHz to 2.4 GHz antenna systems
- WiMAX

Parameter	Min	Тур	Max	Units
Frequency Range	DC		3000	MHz
Insertion Loss	.1	.2	.4	dB
VSWR		1.2 : 1		
DC Breakdown Voltage	72	90	108	V
Impulse Discharge (5 times, 8/20 µsec)	6000			А
Impedance		50		Ohm
Insulation Resistance (DC 100 V)	50			Meg Ohm
Input Power (@2.4 GHz)			42	W
Operating Temperature	-40		+85	°C
Weight		5.8 (164)		oz (g)
Dimensions (includes connectors)		2.75 x 1.25 x 1.75 (70 x 32 x 44)		in (mm)

SYSTEM ORDERING:

SP3-90-6-BFF DC to 3000 MHz, 6 KA, bulkhead N female to N female, 90 V surge protector SP3-90-6-BFM DC to 3000 MHz, 6 KA, bulkhead N female to N male, 90 V surge protector

NOTES:

All shipments F.O.B. Schaumburg, IL 60173

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941 IAS-EUSales@lairdtech.com

Asia: ++86.21.5855.0827.127 IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-SP3-90-6_0414

Any information furnished by Laird and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird matkes no waranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird, Laird Technologies, tor on any of its affiltates or agents shall not be liable for incidental a consecutive and in the products of any specific or general latenses or any indi. All fluids products are subjected to the subject on total charlental or consecutive and specific and the subject on the charlental or consecutive and specific and the subject in the charlental or any indi. All fluids products are subjected to the accurate materials and products are subjected to the accurate the subject on the charlental or consecutive and specific and the subject on the charlental or consecutive and security and the matching and the transformation or any individual and products are subjected tradematics or registers and conditions of sale in effect from time to time, a copy of which will be transford products and any later and the ranks are trademarks or registered trademarks or registered trademarks or registered trademarks are failed fectonologies. Inc. and affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.