



PANEL CUT-OUT		
Z	Y	X
0.70~1.25	12.90~13.10	18.9~19.1
1.25~2.00	12.90~13.10	19.1~19.2

NOTES:
1. Rating:

CCC 6A 250VAC
6(8)A 250VAC
8A/128A 250VAC T105/55
UL CUL
10GPA 125VAC
6GPA 250VAC T105/55

- VDE ENEC 6(4)A 250VAC T85/55
KC 6(4)A 250VAC T85/55
2. Circuit Diagram: 2P ON-OFF
3. Terminal Strength: $\geq 80\text{N}$
4. Electrical life: ≥ 10000 cycles
5. Withstand Voltage: $\geq 1500\text{VAC}$ 1min
Terminals to Button: 3000VAC 1min
6. Leakage Current: 1mA
7. Current resistance: $\leq 50\text{m}\Omega$ (initial)
8. Insulation resistance: $\geq 100\text{M}\Omega$
9. Body Material: NYLON 66 94V-2-0

深圳市华灿天禄电子有限公司

普通公差:
COMMON TOLERANCE:

REV.	DATE	REVISION DESCRIPTION	ISSUE	UP TO 5	±0.20	UNIT	mm	投影	核影	品名	规格	比例
A4				UP TO 5	±0.20	UNIT	mm	核影	核影	规格板开关	RS601	Free
A3				ABOVE 5 TO 30	±0.30	DRAWN BY	周金勇	核影	核影	梁金勇	RS601	
A2				ABOVE 30	±0.50	CHECKED BY	周培雷	核影	核影	周培雷	RS601BK-1010011BB	
A1				ANGULAR	±5°	DATE	2017.08.18	核影	核影			
REV.						APPROVAL BY						