9001KA22 PUSH BUTTON CONTACT 600VAC 10A 30MM T-K

Main

Device short name	К
Mounting diameter	1.2 in (30 mm)

Complementary

Line Rated Current	10 A
Contact operation	Standard without fingersafe
Electrical connection	Screw terminals binder head

Environment

Product Certifications	CE[RETURN]CSA LR24590 class 3211 03[RETURN]UL listed file E42259 CCN NKCR
Trouble Softmontone	

Ordering and shipping details

Category	US10CS121434
Discount Schedule	0CS1
GTIN	785901343899
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.540 in (6.452 cm)
Package 1 Width	1.0000000000 in (2.54 cm)
Package 1 Length	6.452 in (16.387 cm)
Package 1 Weight	0.960 oz (27.216 g)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	[™] China RoHS Declaration

RoHS exemption information	₽¥Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Contractual warranty	
Warranty	18 months