

#### **FASTON**

TE Internal #: 165616-5

Receptacle, 15.5 - 13.5 AWG Wire Size, 1.5 - 2.5 mm<sup>2</sup> Wire Size, 3000 - 4914 CMA Wire Size, Mating Tab Width 2.79 mm [.11 in],


Quick Disconnects

View on TE.com >




Terminals & Splices > Quick Disconnects











Quick Disconnect Terminal Type: Receptacle

Wire Size: 3000 – 4914 CMA

Mating Tab Width: 2.79 mm [ .11 in ]

### **Features**

### **Product Type Features**

| Insertion Force                | Normal          |
|--------------------------------|-----------------|
|                                | NOTITIAL        |
| Configuration Features         |                 |
| Connection Capacity            | Single          |
| Electrical Characteristics     |                 |
| Voltage Rating                 | 300 V           |
| Body Features                  |                 |
| Insulation Material            | Nylon           |
| Contact Features               |                 |
| Quick Disconnect Terminal Type | Receptacle      |
| Mating Tab Width               | 2.79 mm[.11 in] |
| Mating Tab Thickness           | .51 mm[.02 in]  |
| Terminal Orientation           | Straight        |
| Contact Base Material          | Phosphor Bronze |
| Terminal Plating Material      | Tin             |
| Crimp Type                     | Compression     |



| Barrel Type                          | Closed              |
|--------------------------------------|---------------------|
| Termination Features                 |                     |
| Product Terminates To                | Wire & Cable        |
| Mechanical Attachment                |                     |
| Wire Insulation Support              | With                |
| Mating Retention Type                | Dimple              |
| Dimensions                           |                     |
| Product Length                       | 19.8 mm[.779 in]    |
| Compatible Insulation Diameter Range | 4.3 mm[.169 in]     |
| Wire Size                            | 3000 – 4914 CMA     |
| Usage Conditions                     |                     |
| Insulation Option                    | Partially Insulated |
| Operating Temperature Range          | 105 °C[221 °F]      |
| Packaging Features                   |                     |
| Packaging Quantity                   | 1000                |
| Packaging Method                     | Loose Piece         |
| Other                                |                     |
|                                      |                     |

## **Product Compliance**

Barrel Color

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per<br>homogenous material. Also BFR/CFR/PVC<br>Free                                 |
| Solder Process Capability                     | Not applicable for solder process capability  |
|   |   |

Blue

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**















# **Customers Also Bought**



















### **Documents**

### **Product Drawings**

110 PIDG FASTON REC

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_165616-5\_E.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_165616-5\_E.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_165616-5\_E.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.