



+ RELAYS, CONTACTORS & SWITCHES

PROTECTIVE RELAYS



✓ Active

TE CONNECTIVITY (TE)

WOVT3-240=WILMAR OVERVOLTAGE 3

CII | WOVT

WOVT3-240

TE Internal Number: 5-1618108-8

Not EU RoHS Compliant

Not EU ELV Compliant

Contact Arrangement 1 Form A, SPST-NO, 1 NO

Contact Current Rating (A) 5

Input Voltage (VAC) 240

Time Delay With

Phase Three

DOCUMENTATION

No documentation available.

FEATURES

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

Protection Function Overvoltage

Time Delay With

Phase Three

Product Type Relay

Relay Type Protective Relay

Electrical Characteristics

Input Voltage (VAC) 240

Actuating System AC

Signal Characteristics

Frequency Adjustment (Hz) 50 – 400

Contact Features

Type of Control Potentiometer Adjustable

Contact Arrangement 1 Form A, SPST-NO, 1 NO

Contact Current Rating (A) 5

Contact Arrangement (Additional Output) 1 Form B, SPST-NC, 1 N/C

Dimensions

Dimensions (L x W x H) (Approximate) 107.95 x 114.3 x 76.2 mm [4.25 x 4.5 x 3 in]

Usage Conditions

Operating Temperature Range (°C) -40 – 70

Operation/Application

Mode of Operation Adjustable Pick-Up

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF
