



SPECIFICATIONS:

Impedance: 50 Ohms
 Frequency Range: DC~3G
 VSWR: 1.3max
 Working Voltage: 500V RMS @ SEA level
 Insulation Resistance: 5000 Ohms min
 Temperature Range: -55°C TO +155°C
 Drawings products are in line with ROHS standards

| | | | | |
|----|-----------------|----------|----------|-----|
| C | INSULATOR | POM | NONE | 1 |
| B | CONTACT PLATING | BRASS | GOLD | 1 |
| A | BODY | ZINC | NICKEL | 1 |
| ND | DESCRIPTION | MATERIAL | FINISHED | QTY |

NOTE:

| | | | | |
|-----------|-------------|-----------|------------------------------|--------------------------------|
| DRAWN | Zelin. CHEN | Tolerance | I I X I X X Angular | ±0.15 ±0.10 ±0.05 ±5° |
| CHECKED | | View | | |
| APPROVALS | | UNIT | | MM |
| | | SCALE | | 1:1 |

| | | | | |
|-------------|-------------|----------------|------------|------------|
| Product NO. | | DOSIN-801-0032 | | |
| REV | DESCRIPTION | DWN | DATE | APPROVEN |
| A | First Issue | Mr. CHEN | 2015/05/19 | John Kline |
| B | | | | |

DOSIN *Dosin Industrial (H.K.) Ltd*
 东莞市长安五金电子有限公司
 Dosin Hardware Electronics Co., Ltd
 E-mail: dosin2005@163.com
 dosin2005@dosin-hk.com
 Tel: (0086) 769-81153905
 Fax: (0086) 769-81876836

Name: **BNC CONNECTOR**

SIZE A Product NO. DOSIN-801-0032

Date/Time 2015/05/19

CAD FILE H/company drawings/BD

SHEET: 1 OF 1

PCB HOLE CONFIGURATION
 RECOMMENDED PANEL CUTOUTS