


PCB LAYOUT

SPECIFICATIONS

1. Current Rating: 3A AC, DC
2. Voltage Rating: 250V AC, DC
3. Temperature Range: -25°C ~ +85°C
4. Contact Resistance: 20mΩ Max
5. Insulation Resistance: 1000mΩ Min
6. Withstanding Voltage: 1000V AC/minute
7. Material: Wafer LCP, PA6T UL94-V0
PIN Brass Tin-plated
Solder and Phosphoric bronze Tin-plated

Circuit	Part NO.	Dimensions mm		
		A	B	C
2	HC-XH-2ALT-X	2.50	7.50	10.00
3	HC-XH-3ALT-X	5.00	10.00	12.50
4	HC-XH-4ALT-X	7.50	12.50	15.00
5	HC-XH-5ALT-X	10.00	15.00	17.50
6	HC-XH-6ALT-X	12.50	17.50	20.00
7	HC-XH-7ALT-X	15.00	20.00	22.50
8	HC-XH-8ALT-X	17.50	22.50	25.00
9	HC-XH-9ALT-X	20.00	25.00	27.50
10	HC-XH-10ALT-X	22.50	27.50	30.00
11	HC-XH-11ALT-X	25.00	30.00	32.50
12	HC-XH-12ALT-X	27.50	32.50	35.00
13	HC-XH-13ALT-X	30.00	35.00	37.50
14	HC-XH-14ALT-X	32.50	37.50	40.00
15	HC-XH-15ALT-X	35.00	40.00	42.50
16	HC-XH-16ALT-X	37.50	42.50	45.00

Ordering Information



			GENERAL TOLERANCE		制图 DRAWING		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD			
			DIM	TOL	审核 CHECK					
			X.X	±0.30	批准 APPROVAL		产品名称 TITLE	XH(TJC3) 立贴	版本 REV.	A
			X.XX	±0.20	比例 SCALE		产品料号 PART NO.	HC-XH-NALT-X	单位 UNITS	mm
			X.XXX	±0.10	投影 Projection		材料 MATERIAL		页次 SHEET	1/1
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle	±3.0°						