# GA10K3435DM010 ACTIVE

#### **MEAS**

TE Internal #: GA10K3435DM010

TE Internal Description: PRO4-OVERMOLDED PROBE

View on TE.com >



Sensors > Temperature Sensors > NTC Thermistors Sensors & Probes > NTC Probes



NTC Probe Type: HVAC/R

Electrical Connection: Open End

Resistance (at 25°C):  $10 \text{ k}\Omega$  $\beta$ -Value(25/85): 3435 K

Accuracy (at T\_ref): ± .22 @ 25 °C

## **Features**

## **Product Type Features**

Wire/Cladding Type	24 AWG Stranded Insulated Leads
NTC Probe Type	HVAC/R
Sensor Package	Overmold TPE
Configuration Features	
Electrical Connection	Open End
Electrical Characteristics	
<b>β</b> -Value(25/85)	3435 K
Mechanical Attachment	
Wire Length	1000 mm[39 in]
Usage Conditions	
T_ref for Resistance	25 °C[77 °F]
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]
Resistance (at 25°C)	10 kΩ
Accuracy (at T_ref)	± .22 @ 25 °C
Tolerance Resistance	± 1 %

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Pb (20% in Component part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





# Customers Also Bought






















### **Documents**

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_GA10K3435DM010\_4.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_GA10K3435DM010\_4.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_GA10K3435DM010\_4.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

TPE OM NTC Probe 5x20mm

English