


FEATURES

- Rating to 1000V PRV
- Surge overload rating to 400 Amperes peak
- Ideal for printed circuit board
- Reliable low cost construction utilizing molded plastic technique results in inexpensive product
- Lead solderable per MIL-STD-202 method 208



KBU		
Dim	Min	Max
A	22.80	23.20
A1	3.70	4.10
B	18.90	19.30
B1	17.60	18.00
C	6.55	6.85
C1	4.50	4.80
E	Ø1.20	Ø1.40
F	25min	
F1	4min	
K	4.70	5.30
All Dimensions in mm		

Maximum Ratings (@TA = 25°C unless otherwise specified)

Characteristic	Symbol	KBU25005	KBU2501	KBU2502	KBU2504	KBU2506	KBU2508	KBU2510	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward Output current @TA=25°C	$I_{F(AV)}$	25.0							A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load	I_{FSM}	400							A
I ² t Rating for fusing @Tj=25°C	I ² t	664							A ² S

Thermal Characteristics

Characteristic	Symbol	KBU25005	KBU2501	KBU2502	KBU2504	KBU2506	KBU2508	KBU2510	UNITS
Typical thermal resistance	$R_{\theta JA}$ $R_{\theta JC}$	18 1.4							°C/W
Operating junction temperature range	T_J	- 55 ---- + 150							°C
Storage temperature range	T_{STG}	- 55 ---- + 150							°C

Electrical Characteristics (@TA = 25°C unless otherwise specified)

Characteristic	Symbol	KBU25005	KBU2501	KBU2502	KBU2504	KBU2506	KBU2508	KBU2510	UNITS
Maximum instantaneous forward voltage @12.5.0A @25.0A	V_F	1.0 1.1							V
Maximum reverse current @TA=25°C at rated DC blocking voltage @TA=100°C	I_R	5.0 0.5							μ A m A

RATINGS AND CHARACTERISTICS CURVES

($T_A=25^\circ\text{C}$ unless otherwise noted)

FIG1: I_o - T_c Curve




FIG2: Surge Forward Current Capability




FIG3: Instantaneous Forward Voltage





FIG4: Typical Reverse Characteristics



Device	Package	Shipping
KBU25005-KBU2510	KBU	400 Units/Box