


Printview: Triple-deck terminal block; 6-conductor through terminal block; N; without marker carrier; for Ex e II and Ex i applications; internal commoning; conductor entry with violet marking; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP® - Item No.: 2002-3209



**Triple-deck terminal block; 6-conductor through terminal block; N; without marker carrier; for Ex e II and Ex i applications; internal commoning; conductor entry with violet marking; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP®**

Item No.: 2002-3209



*Triple-deck terminal block; 6-conductor through terminal block; N; without marker carrier; for Ex e II and Ex i applications; internal commoning; conductor entry with violet marking; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP®*

## Marking

RoHS ✓  
Compliant

## Business data

|                      |               |
|----------------------|---------------|
| Supplier             | WAGO          |
| Item no.             | 2002-3209     |
| GTIN / EAN           | 4045454417161 |
| Content              | 1             |
| Order amount         | 50            |
| Customer item number |               |

## Notes

## Technical data

### Miscellaneous

|                             |                  |
|-----------------------------|------------------|
| Ratings per                 | IEC/EN 60947-7-1 |
| Rated voltage (III / 3) [V] | 500 [V]          |

Printview: Triple-deck terminal block; 6-conductor through terminal block; N; without marker carrier; for Ex e II and Ex i applications; internal commoning; conductor entry with violet marking; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP® - Item No.: 2002-3209

| <b>Technical data</b>   |   |
|---|---|
| <i>Rated impulse voltage (III / 3) [kV]</i>                         | 6 [kV]  |
| <i>Rated current [A]</i>  | 24 [A]  |
| <i>Rated current (2) [A]</i>  | 28 [A]  |
| <i>Rated voltage EN (Ex e II) [V]</i>                               | 440 [V]   |
| <i>Rated current (Ex e II) [A]</i>                                  | 19 [A]  |
| <i>Rated current (Ex e II) with jumper [A]</i>                      | 17 [A]  |
| <i>Legend (ratings)</i>   | (III / 3) Overvoltage category III / Pollution degree 3 |
| <i>Connection technology</i>  | Push-in CAGE CLAMP®                                     |
| <i>Actuation type</i>   | Push-in   |
| <i>Connectable conductor materials</i>                              | Copper  |
| <i>Nominal cross section</i>  | 2.5 mm <sup>2</sup>                                     |
| <i>Solid conductor</i>  | 0.25 ... 4 mm <sup>2</sup> / 22 ... 12 AWG              |
| <i>Solid conductor, push-in termination</i>                         | 0.75 ... 4 mm <sup>2</sup> / 18 ... 12 AWG              |
| <i>Fine-stranded conductor</i>                                      | 0.25 ... 4 mm <sup>2</sup> / 22 ... 12 AWG              |
| <i>Fine-stranded conductor with ferrule, push-in termination, f</i> | 0.75 mm <sup>2</sup> / 18 AWG                           |
| <i>Strip length</i>   | 10 ... 12 mm / 0.39 ... 0.47 Inch                       |
| <i>Total number of connection points</i>                            | 6   |
| <i>Total number of potentials</i>                                   | 1   |
| <i>Number of levels</i>   | 3   |
| <i>Type of wiring</i>   | Front-entry wiring                                      |
| <i>Width</i>  | 5.2 mm / 0.205 Inch                                     |
| <i>Height from upper-edge of DIN-35 rail</i>                        | 69.5 mm / 2.736 Inch                                    |
| <i>Depth</i>  | 93.3 mm / 3.673 Inch                                    |
| <i>Design</i>   | horizontal  |
| <i>Type of mounting</i>   | Carrier rail 35 x 15                                    |
| <i>Potential marking</i>  | N   |
| <i>Marking level</i>  | Center/side marking                                     |
| <i>Color</i>  | blue  |
| <i>Insulating material</i>  | Polyamide 66 (PA 66)                                    |
| <i>Fire load [MJ]</i>   | 0.321 [MJ]  |
| <i>Weight [g]</i>   | 17.745 [g]  |
| <i>Packaging type</i>   | BOX   |

Printview: Triple-deck terminal block; 6-conductor through terminal block; N; without marker carrier; for Ex e II and Ex i applications; internal commoning; conductor entry with violet marking; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP® - Item No.: 2002-3209

---



**Technical data**

|                              |  |
|------------------------------|--|
| <i>Product Family</i>        | <i>TOPJOB® S</i>                       |
| <i>Main product function</i> | <i>Multilevel terminal blocks</i>      |
| <i>Product type</i>          | <i>Through rail-mount term. blocks</i> |



Printview: Triple-deck terminal block; 6-conductor through terminal block; N; without marker carrier; for Ex e II and Ex i applications; internal commoning; conductor entry with violet marking; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP® - Item No.: 2002-3209

---

## Images & drawings



Printview: Triple-deck terminal block; 6-conductor through terminal block; N; without marker carrier; for Ex e II and Ex i applications; internal commoning; conductor entry with violet marking; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP® - Item No.: 2002-3209



Printview: Triple-deck terminal block; 6-conductor through terminal block; N; without marker carrier; for Ex e II and Ex i applications; internal commoning; conductor entry with violet marking; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP® - Item No.: 2002-3209

---

## Address

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27

32423 Minden

Telefon: 0571/887-0

Fax: 0571/887-169

<http://www.wago.com>

© WAGO Kontakttechnik GmbH & Co. KG

Technische Änderungen und Irrtümer vorbehalten.