

Low Pass Filter

RLP-120+

50Ω DC to 120 MHz

Maximum Ratings


Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power Input	0.5W Max

Permanent damage may occur if any of these limits are exceeded.

Pin Connections

RF IN	2
RF OUT	6
GROUND	1, 3, 4, 5, 7, 8

Outline Drawing





Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J
.350	.350	.100	.175	.075	.100	.110	.040	.080
8.89	8.89	2.54	4.45	1.91	2.54	2.79	1.02	2.03
K	L	M	N	P	Q	R	wt.	
.050	.040	.195	.390	.120	.390	.070	grams	
1.27	1.02	4.95	9.91	3.05	9.91	1.78	0.25	

Note: Please refer to case style drawing for details

Demo Board MCL P/N: TB-332 Suggested PCB Layout (PL-176)



Features

- high rejection
- sharp insertion loss roll off
- excellent VSWR, 1.1:1 typ. @ passband
- aqueous washable

Applications

- wireless communications
- receivers / transmitters



Generic photo used for illustration purposes only
CASE STYLE: GP731

+RoHS Compliant


The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Reel Size	Devices/Reel
7"	10, 20, 50, 100, 200
13"	500, 1000


Low Pass Filter Electrical Specifications (T_{AMB} = 25°C)

PASSBAND (MHz)	f _{co} , MHz Nom.	STOPBAND (MHz)		VSWR (:1)	
		(Loss > 20dB)	(Loss > 40dB)	Passband Typ.	Stopband Typ.
DC - 120	132	170 - 205	205 - 1000	1.1	20

Typical Frequency Response





Functional Schematic



Typical Performance Data at 25°C

Frequency (MHz)	Insertion Loss (dB)		Return Loss (dB)	Frequency (MHz)	Group Delay (nSec)
	\bar{x}	σ			
0.5	0.20	0.07	29.54	2.0	6.07
50.0	0.41	0.07	32.03	5.0	5.81
80.0	0.65	0.07	22.39	10.0	5.80
100.0	0.82	0.07	36.60	20.0	5.89
120.0	1.27	0.08	27.95	25.0	5.85
128.0	1.98	0.11	12.31	45.0	6.25
132.0	2.99	0.19	7.34	50.0	6.32
135.0	4.25	0.27	4.91	55.0	6.35
142.0	8.65	0.38	2.09	60.0	6.53
150.0	14.69	0.40	1.10	65.0	6.67
160.0	22.03	0.40	0.74	70.0	6.73
170.0	28.86	0.40	0.60	75.0	7.05
180.0	35.38	0.43	0.49	80.0	7.24
205.0	52.34	0.80	0.39	90.0	7.92
300.0	64.61	0.74	0.20	100.0	8.66
500.0	69.37	2.02	0.12	110.0	9.97
800.0	78.88	8.13	0.13	120.0	12.56
1000.0	75.79	5.98	0.17	125.0	14.78



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

